

SAFETY DATA SHEET TG.0118.500 Garrards Pre-Con 10 Aerosol

SECTION 1: Identification: Product identifier and chemical identity

Product identifier

Product name TG.0118.500 Garrards Pre-Con 10 Aerosol

Relevant identified uses of the substance or mixture and uses advised against

Application Aerosol Spray Adhesive

Details of the supplier of the safety data sheet

Supplier +61 7 3881 1693

Garrards PTY LTD

PO Box 5477, BRENDALE MDC, QLD, 4500

Emergency telephone number

Emergency telephone National Poison Line AU 13 11 26

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Gas 2 - H221 Press. Gas, Compressed - H280 Flam. Liq. 3 - H226

Health hazards Eye Irrit. 2A - H319 STOT SE 3 - H336

Environmental hazards Aquatic Acute 2 - H401 Aquatic Chronic 2 - H411

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following

overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Hazard pictograms









Signal word

WARNING

Hazard statements

H221 Flammable gas.

H280 Contains gas under pressure; may explode if heated.

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

TG.0118.500 Garrards Pre-Con 10 Aerosol

Precautionary statements

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.

P240 Ground/ bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/ container in accordance with national regulations.

Contains

methyl acetate, heptane, n-Hexane

Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

SECTION 3: Composition and information on ingredients

Mixtures

Petroleum gases, liquefied

30-60%

CAS number: 68476-85-7

Classification

Flam. Gas 1 - H220

Press. Gas, Liquefied - H280

methyl acetate 20-30%

CAS number: 79-20-9

Classification

Flam. Liq. 2 - H225

Eye Irrit. 2A - H319

STOT SE 3 - H336

Revision date: 16/03/2020 Revision: 4 Supersedes date: 15/03/2020

TG.0118.500 Garrards Pre-Con 10 Aerosol

heptane 1-5%

CAS number: 142-82-5

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

n-Hexane 1-5%

CAS number: 110-54-3

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373

Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

Description of first aid measures

General information Remove affected person from source of contamination. Place unconscious person on their

side in the recovery position and ensure breathing can take place. Get medical attention if any

discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

Ingestion Get medical attention immediately. Never give anything by mouth to an unconscious person.

Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a

position comfortable for breathing.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the

person is conscious, coherent and they can remove them themselves If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get

medical attention promptly. Show this Safety Data Sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed

Inhalation May cause coughing and difficulties in breathing. May cause eye and respiratory system

irritation. Overexposure may depress the central nervous system, causing dizziness and

intoxication.

Revision date: 16/03/2020 Revision: 4 Supersedes date: 15/03/2020

TG.0118.500 Garrards Pre-Con 10 Aerosol

Ingestion Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may

cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or

vomiting may cause chemical pneumonitis.

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. The liquid is

irritating to eyes and skin. A single exposure may cause the following adverse effects:

Dryness and/or cracking.

Eye contact Causes serious eye irritation. Burns can occur. A single exposure may cause the following

adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged

contact causes serious eye and tissue damage.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C. Containers can

burst violently or explode when heated, due to excessive pressure build-up. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source

of ignition and flash back.

Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. No smoking, sparks, flames or other sources of

ignition near spillage.

Environmental precautions

Environmental precautions Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-

combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and

place into containers. Wash thoroughly after dealing with a spillage.

SECTION 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide

adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the

ground.

TG.0118.500 Garrards Pre-Con 10 Aerosol

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the

original container. Pressurized container: Must not be exposed to temperatures above 50°C.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

SECTION 8: Exposure controls and personal protection

Control parameters

Occupational exposure limits

Petroleum gases, liquefied

Long-term exposure limit (8-hour TWA): 1000 ppm 1800 mg/m³

Carc. 1B

heptane

Long-term exposure limit (8-hour TWA): 400 ppm 1640 mg/m³ Short-term exposure limit (15-minute): 500 ppm 2050 mg/m³

n-Hexane

Long-term exposure limit (8-hour TWA): 20 ppm 72 mg/m³
Carc. 1B = Presumed to have carcinogenic potential for humans.

Exposure controls

Protective equipment





Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapours and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates duet fumos are vapour or mist.

dust, fumes, gas, vapour or mist.

Eye/face protection Wear chemical splash goggles.

Hand protection Use protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

smoking and using the toilet. Wash promptly with soap and water if skin becomes

contaminated. Promptly remove any clothing that becomes contaminated. When using do not

eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Revision date: 16/03/2020 Revision: 4 Supersedes date: 15/03/2020

TG.0118.500 Garrards Pre-Con 10 Aerosol

Appearance Aerosol.

SECTION 10: Stability and reactivity

Stability Stable at normal ambient temperatures and when used as recommended.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Oxidising agents. Reducing agents.

Hazardous decomposition

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

products

Hydrogen chloride (HCI). Nitrous gases (NOx).

SECTION 11: Toxicological information

SECTION 12: Ecological information

SECTION 13: Disposal considerations

Waste treatment methods

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

Air transport notes Passenger Aircraft/Rail <75 kg. Cargo Aircraft Only <150 kg

UN number

UN No. (ICAO) 1950

UN proper shipping name

Proper shipping name

(IMDG)

AEROSOLS, FLAMMABLE (PROPANE, ISOBUTANE) 2.1, LTD QTY

Proper shipping name (ICAO) AEROSOLS, FLAMMABLE (PROPANE, ISOBUTANE) 2.1, LTD QTY

Transport hazard class(es)

Transport labels



SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009)

No. 716).

Guidance CHIP for everyone HSG228.

Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

SECTION 16: Any other relevant information

Revision date 16/03/2020

Revision 4

TG.0118.500 Garrards Pre-Con 10 Aerosol

Supersedes date 15/03/2020

SDS No. 22129

Hazard statements in full H220 Extremely flammable gas.

H221 Flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life. H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

DIRECTIONS FOR USE

PRODUCT LOGO

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.