

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Flick guard™

TERMITE PROTECTION

ACTIVE CONSTITUENT:
2.0 g/kg DELTAMETHRIN
(Equivalent to 1 g/m² deltamethrin)

GROUP 3A INSECTICIDE

For the protection of buildings and structures from subterranean termites in accord with the Australian Standard Series AS 3660 - Termite management.

MANUFACTURED BY:

Ensystem Australia Pty Ltd
ABN 92 096 839 815
Unit 3 The Junction Estate,
4-6 Junction Street AUBURN NSW 2144

DISTRIBUTED BY:

Flick Anticimex
Unit 9, 145 Arthur Street,
HOMEBUSH WEST NSW 2140
APVMA Approval No: 59139/130643

CUSTOMER SERVICE **13 35 36**
EMERGENCY RESPONSE (ALL HOURS) **13 35 36**

www.Flickguard.com.au

Flick guard™

TERMITE PROTECTION

DIRECTIONS FOR USE

SITUATION	PEST	STATE	RATE	CRITICAL COMMENTS
Domestic, commercial, industrial, and public buildings to form a complete pre-construction treatment providing both termite and moisture protection or as a flexible termite management system that may be used as part of an integrated termite management program.	Subterranean termites.	All States except TAS.	Single strip thickness is sufficient to form an effective barrier.	Flickguard must be installed as a complete and continuous barrier. Any gaps or tears present in the strips after installation must be repaired as per the General Instructions. For complete under slab strip installations, installers should select an appropriate width strip to minimise the number of joins needed to complete the installation. For joining strips, attaching strips to surfaces and treatment of penetrations, see General Instructions. For specific details on installation of strips for full under slab treatments, perimeter treatments, service penetrations, retaining walls and construction joints see General Instructions.

Note: Recommendations to undertake annual inspections must be stated on the durable notice required by the Building Code of Australia (BCA).

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORIZED UNDER APPROPRIATE LEGISLATION.

GENERAL INSTRUCTIONS

Flickguard is a professional termite protection system for new structures and extensions to existing structures. The purpose of Flickguard is to deter concealed entry by subterranean termites from the soil into the structure above the termite barrier as per the Australian Standard Series AS 3660 Termite management. Use Flickguard to establish a continuous barrier between the structure and any termite colonies in accord with AS 3660. A great deal of care is required to understand the construction details of the building and to install Flickguard in a manner which ensures this complete and continuous barrier.

Flickguard strips may be cut to size in order to fit different building construction methods and systems.

Flickguard may be installed as a complete underslab treatment providing both termite and moisture protection or as a flexible termite management system that can be used as part of a complete termite management program. If Flickguard is used in combination with a concrete slab acting as a physical termite barrier, the slab must be poured in accordance with Australian Standard AS 2870 Residential slabs and footings.

Prior to Installation

Prior to installing Flickguard it is recommended that a site inspection is performed and the following precautions are carried out.

- Eliminate any active nest of an economically important species of subterranean termite found within the property boundary up to a distance of 50 m from the proposed new building work.
- Excavate all tree stumps, logs, and roots and remove from the building footprint.
- Remove all timber off-cuts, building debris, removable framework and other waste materials from the area where the Flickguard is to be installed.

Joining Strips

In most situations Flickguard is held in place by construction materials as the structure is built. For instance, under-slab installations are held in place by the slab itself exhibiting downward pressure. In such cases adhesives or bonding agents used to join strips are required until these construction components are installed. In situations where construction materials do not exert pressure on strip overlaps such as perimeter cavities, a permanent bond must be created.

Such a bond can be made using TRITHOR MAXX Termiticidal Contact Adhesive Spray, which has been documented to demonstrate meeting Australian Standard 3660 – Termite management. Ensure that a minimum of 200 mm overlap is achieved when joining.

Repairing Tears or Gaps

If the strip is ripped or torn it must be repaired by applying a single strip

of sufficient size to fully cover the gap or tear plus a minimum overlap of 50 mm. The repair strip is bonded onto the tear/gap as detailed above in Joining Strips.

Complete Under-slab Treatment

Flickguard provides both termite and moisture protection when installed as a complete under-slab treatment. Install the strips on top of the bedding sand prior to laying steel reinforcing mesh. The green layer should be on top and the red layer should be underneath. Ensure there is enough overlapping Flickguard at the slab edge to allow full moisture and termite protection. Care should be taken to ensure no holes are made in the strip when laying the steel mesh. The concrete is then poured on top of the Flickguard.

Perimeter Treatment

In-fill Slab

Secure the Flickguard to the outer edge of the brickwork and fold the strip over the top of the brickwork securing it to the internal brickwork towards the footings. Ensure that prior to the slab being poured that the strip is securely held in place using TRITHOR MAXX Termiticidal Contact Adhesive Spray. The damp proof course is installed above the Flickguard. The green layer should face outwards with the red layer against the building.

Rebated slab edge

Flickguard should be installed before the timber frame has been raised. Attach one edge of the strip to the slab to ensure the frame bottom plate will be placed on top of the strip using an appropriate adhesive or bonding agent. The second edge is fixed to the upper surface of the brickwork with the outside leading edge being visible in the damp proof course (DPC) horizontal mortar joint using an appropriate adhesive or bonding agent designed by the manufacturer to provide a construction grade bond between the strip and the material it is being bonded to. Any excess Flickguard is installed into the cavity. The green layer should face outwards with the red layer against the building.

Corners

Corners must be carefully installed ensuring the finished corner is smooth and the Flickguard is continuous. Use Flickguard pre-formed corners or construct using the Flickguard Strips. Make slits from the edge of the strip into the corner of the slab to allow folding of the strip around the corner. At a corner two strips must be joined and sealed using TRITHOR MAXX Termiticidal Contact Adhesive Spray with a minimum of 50 mm overlap.

Service Penetrations

To protect penetrations use Flickguard pre-formed penetration collars. Place the pre-formed collars over the pipe penetrations ensuring the base will sit in the concrete slab when poured. Two cable ties are used to secure the seal around the penetration. Ensure there are no gaps between the moisture membrane, the Flickguard pre-formed collars and the penetrations.

Termite Caps and Strip Shielding

Termite shields are installed on all subfloor structures such as piers, posts, stumps and walls, below the underside of the lowest floor framing member or suspended concrete slab, to provide a continuous barrier. Strips of Flickguard are fitted to allow for a minimum overhang of 40 mm on all exposed sides in the subfloor region. When joining Flickguard Strips they must be sealed using TRITHOR MAXX Termiticidal Contact Adhesive Spray. The green layer is placed uppermost and the red layer face down.

Retaining Walls

Flickguard can be used as a termite barrier when installed against a retaining wall. Flickguard does not negate the necessity for installation of conventional water-proofing materials. Flickguard should be installed down to the base of the wall plus 200 mm across the footing, in order to cover the base course mortar joint, and is then secured to the external concrete/brickwork. All joints and edges must be sealed using TRITHOR MAXX Termiticidal Contact Adhesive Spray. The red layer is designed to face the retaining wall and the green layer to face the soil/fill.

Construction Joints

Install a minimum of 300 mm wide strip of Flickguard immediately under the construction joint by adhering it to the moisture membrane. If Flickguard is being used in a continuous manner as the moisture membrane, there is no need for installing an additional strip under the construction joint. The Flickguard strip must be located central to the construction joint. The green layer is placed uppermost and the red layer face down.

For Existing Masonry/ Concrete to New Concrete Joints – incl. additions, paths, etc.

Fix one edge of the Flickguard strip to the existing vertical edge surface using TRITHOR MAXX Termiticidal Contact Adhesive Spray. The Flickguard strip must start within 20 mm of the upper edge of the new concrete. Adhere all joints and ensure that the Flickguard strip remains continuous towards the footing and for at least 150 mm horizontally under the new concrete. It must be adhered to the upper surface of the moisture membrane using TRITHOR MAXX Termiticidal Contact Adhesive Spray.

Service Requirements:

Regular competent inspections are strongly recommended as part of an ongoing termite management program. Service requirements should be determined as a result of at least an annual inspection by a licensed professional pest manager. More frequent inspections may be required in high-risk termite areas.

To minimise the risk of termite infestation, the subfloor area of buildings should be kept free of stored or waste timber and all other building materials that attract termites. Appropriate action should also be taken to eliminate any undue dampness caused by leaking water or sewerage pipes, or inadequate drainage. Flickguard will provide at least eight years protection.

PROTECTION OF WILDLIFE, FISH, CRUSTACEANS AND ENVIRONMENT:

DO NOT contaminate streams, rivers or waterways with the product or the used container.

STORAGE AND DISPOSAL:

Store in the original packaging in a cool well-ventilated area. Do not store for prolonged periods in direct sunlight. Dispose of unused off-cuts by laying over the Flickguard barrier at an installation site and cover with concrete slab or place in cavity wall. If this is not possible, off-cuts should be placed in a sealed plastic bag and disposed of via an approved industrial waste disposal site. Puncture and deliver empty packaging to an approved waste management facility in compliance with relevant local, state or territory government regulations. Do not burn empty containers or product.

SAFETY DIRECTIONS:

Do not touch or rub eyes, nose or mouth with hand. Facial skin contact may cause temporary numbness. Wash hands after use.

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre. Phone Australia 13 11 26, New Zealand 0800 764 766.

SDS:

Additional information is listed in the Safety Data Sheet which is available from Ensyslex on request. Call Customer Service 13 35 36.

NOTICE

Ensyslex warrants that this product conforms to its description and is reasonably fit for the purposes stated on the label when used in accordance with Directions for Use under normal conditions of use. No warranty of merchantability or fitness for a particular purpose, express or implied, extends to the use of the product contrary to label instructions or under off-label permits not endorsed by Ensyslex, or under abnormal conditions.