

Blockaid-Aqua

INDUSTRY LEADING NEW GENERATION
WATERPROOFING TREATMENT

- ✓ RETAINING WALLS
- ✓ PLANTER BOXES
- ✓ ROOFS, BALCONIES & DECKS
- ✓ TERRACES & PODIUMS
- ✓ SHOWER RECESS & BATHROOM WALLS
- ✓ GENERAL WET AREAS
- ✓ INTERIOR OR EXTERIOR USE

Granitgard



Blockaid-Termi

INDUSTRY LEADING
PRE-CONSTRUCTION TERMITE SEALANT

- ✓ JOINTS
- ✓ RETAINING WALLS
- ✓ STEP DOWNS
- ✓ NARROW CAVITIES (PERIMETERS)
- ✓ INDUSTRY-LEADING 50 YEAR WARRANTY*

*50 year warranty subject to conditions

Granitgard
TERMITE MANAGEMENT SYSTEM



BLOCKAID-AQUA

BLOCKAID-AQUA is a highly flexible elastomeric waterproofing treatment designed for use on a wide variety of vertical and horizontal substrates where movement is to be expected.

BLOCKAID-AQUA exceeds the highest standard required for waterproofing wet areas - AS 4858 achieving Class III, making it suitable for a wide range of waterproofing applications.

BLOCKAID-AQUA dries grey with a smooth surface finish and remains highly flexible under extreme elongation and under constant exposure to moisture. Unlike bituminous sealants, **BLOCKAID-AQUA** does not soften and attract dirt and stains and has excellent chemical resistance and durability. It may be easily cleaned with mild detergents and water.

BLOCKAID-AQUA is UV resistant however we recommend the sealant is covered with a suitable acrylic paint for extended outdoor exposure. **BLOCKAID-AQUA** is a soft coating and not suitable for high traffic areas unless covered with a suitable protective covering such as tiles, but will withstand light foot traffic.

Filling Gaps, Cracks & Voids

Smaller cracks and irregularities in surfaces to be treated with **BLOCKAID-AQUA/TERMI** can be cleaned, primed and filled with **BLOCKAID-AQUA/TERMI** direct from a cartridge. If there are numerous or large gaps, cracks or voids in a surface, especially one which is to be treated with a **BLOCKAID-AQUA/TERMI** sealant, then the entire area needs to be treated with **BLOCKAID-AQUA/TERMI**.

Filling Gaps, Cracks & Voids In Concrete

Joints or vertical edges that are formed in unvibrated concrete against timber or metal will have some honeycombing in the surface that is to be treated. Honeycombing if not properly filled can provide an avenue for termites to bypass a Termite treatment and gain concealed entry to a building.

It is critical therefore that a liberal amount of **BLOCKAID-AQUA/TERMI** primer is brushed onto the clean concrete surfaces and as soon as the **BLOCKAID-AQUA/TERMI** primer is dry, a thick bead of **BLOCKAID-AQUA/TERMI** straight from a cartridge is applied onto and worked into (best done with a spatula) all the treated surfaces.

Prime All Surfaces

BLOCKAID-AQUA/TERMI primer must be applied to all the surfaces (horizontal and vertical) that are going to be treated with **BLOCKAID-AQUA/TERMI** in either sealant or gap filling (bead) forms. Application by roller or soft broom works best for larger, smooth surfaces. The **BLOCKAID-AQUA/TERMI** primer must be worked into porous surfaces. This is best done with a soft brush.

Coverage

BLOCKAID-AQUA/TERMI primer has a coverage rate of between six and eight square metres per litre (125 to 160 ml per m²) depending on the porosity of the surface being treated. For very porous surfaces two coats of primer may be required.

Shelf Life

BLOCKAID-AQUA/TERMI primer has a shelf life of twelve months when stored in the original unopened container. Once opened, **BLOCKAID-AQUA/TERMI** primer will be usable for three (3) months, so long as the container lid is tightly resealed after each opening. Storage should be between 5°C and 40°C and out of direct sunlight.

Drying

Drying time for **BLOCKAID-AQUA/TERMI** primer is approximately ten to fifteen minutes at an ambient temperature of 20°. Drying times will vary according to ambient temperature, humidity and porosity of substrate. Primer is dry when it appears clear and not milky-white, as it is when applied.

Phone: 1800 032 549

Email: support@granitgard.com.au
www.granitgard.com.au



9 321647 001870 >

BLOCKAID-TERMI

BLOCKAID-TERMI is an industry leading solvent free termite management system for joints, step downs, narrow cavities (perimeters) and retaining walls. Applied with either a brush, roller or gun, **BLOCKAID-TERMI** is your easy to apply pre-construction termite protection.

Powered by an industry proven long lasting active ingredient - bifenthrin - **BLOCKAID-TERMI** has excellent adhesion and weathering properties combined with durability and flexibility. **BLOCKAID-TERMI** complies with AS3660.1 AS3660.2 AS3660.3 and the Australian standard for wet area membranes AS4858.

BLOCKAID-TERMI offers a full 50* year termite protection warranty.

*Conditions apply, as per warranty documentation and installation manual.

Contents: 330 mL

Contents: 330 mL