



GENERAL SPECIFICATIONS

Model	9 V»	11 V	13 V
Body Capacity	9 yd ³	11 yd³	13 yd³
Body Width (A)	82"	96"	96″
Body Height (B)	71″	72"	72"
Body Length (C)	191.5″	195″	211″
*Approx. Body Weight	9,290 lbs	9,650 lbs	10,012 lbs
Hopper Capacity	2 yd³	2.7 yd³	2.7 yd³
Hopper Opening Width	60"	80"	80"
Loading Sill Height	Frame	Frame	Frame
Hopper Cycle Time	26-30 secs.	22-24 secs.	22-24 secs.

MINIMUM CHASSIS SPECIFICATIONS (STANDARD)

Model	9 V»	11 V	13 V	
**Minimum GVWR	23,000 lbs	26,000 lbs	29,000 lbs	
Cab to Trunnion	84"	84"	102″	

HYDRAULIC CYLINDER SPECIFICATIONS (STANDARD)

Model	9 V»	11 V	13 V	
Slide Cylinders (2)	4"	4"	4"	
Sweep Cylinders (2)	5"	5″	5"	
Tailgate Cylinders (2)	3.5"	3.5"	3.5"	
Ejection Cylinder	3-Stage 5.5"	3-Stage 5.5"	4-Stage 6.5"	

BODY CONSTRUCTION

Roof & Sides	10 gauge	80K GR
Floor (center)	1/4"	50K GR
Floor (sides)	10 gauge	80K GR
Ejection Panel	10 gauge	50K GR
Sweep Panel	1/4"	80K GR
Tailgate (upper & lower)	10 gauge	50K GR
Hopper Floor	1⁄4″	50K GR
Hopper Floor (back)	1/4"	100K GR
Side Panel	7 gauge	50K GR

HYDRAULIC SYSTEMS

Oil Reservoir	45 gal
Oil Flow w/std. pump	25 gpm
Min. Accept. Oil Flow	20 gpm
Operating Pressure	2,350 psi
Engine RPM for STD gpm	1,350-1,550
Hydraulic Hoses	4-to-1 burst
Return Filter	10 micron


» 9 yd³ model will be built with external hydraulic cylinders.

STANDARD EQUIPMENT

- Semi automatic cycling
- Accelerator kit
- Auto-lock tailgate
- Back up alarm
- All LED lights
- Upper rear lights
- Sight gauge on oil tank
- Chrome cylinder rods
- Side access door
- Driver alert buzzer
- Tailgate ajar indicator
- Pump
- Adjustable riding step
- Imron elite productive paint
- Color rear vision camera system

OPTIONAL EQUIPMENT

- Special lighting
- PTO
- Container lifts (commercial & residential)
- Pack at low idle
- Hopper liners
- Upgraded body steel package
- Body scale systems
- CNG fueling system
- Axalta Imron Elite finish paint













^{*}Approximate Body Weight empty and exclusive of options.

^{**} Any Chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted. (Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)