


ROTO PAC[®]

Patent number 10.427.871.



FIRST IN THE WORLD

The ROTO PAC[®] touts the highest legal payload of any automated in the world, and is the first refuse truck that can effectively manage both organics refuse collection and municipal solid waste (MSW). Gone are the days of maintaining separate trucks to meet a community's waste management needs.



GENERAL SPECIFICATIONS

Model	14 R	20 R	25 R	27 R
Body Capacity	14 yd ³	20 yd ³	25 yd ³	27 yd ³
Body Width (A)	96"	96"	96"	96"
Body Height (B)	109"	109"	109"	109"
Body Length (C)	175"	209"	239"	251"
†Raised Tailgate Height	225"	225"	225"	225"
†Body Height (Raised)	211"	235.5"	260.5"	260.5"

MINIMUM CHASSIS SPECIFICATIONS

Model	14 R	20 R	25 R	27 R
*Minimum GVWR	33,000 lbs	50,000 lbs	56,000 lbs	56,000 lbs

PACKER SPECIFICATIONS

Hopper Capacity	5.7 yd ³
Packer Swept Volume	7 yd ³ per min
Minimum Compaction	1,000 lbs per yd ³
Auger Torque	23,000 lb-ft

ARM SPECIFICATIONS

Arm Extension	144"
Arm Lifting Capacity	500 lbs
Arm Cycle Time	8 secs.

BODY CONSTRUCTION

Roof	12 gauge	80K
Sides	12 gauge	80K
Body Floor	3/16"	100K
Tailgate Back / Sides	12 gauge	80K
Hopper Floor/Sides	1/4"	Hardox 400

HYDRAULIC SYSTEM

Oil Reservoir	50 gal
Oil Flow Rate	Body 18 gpm @ 700 RPM Arm 21 gpm @ 700 RPM
Body Operating Pressure	3,800 psi
Arm Operating Pressure	2,200 psi
Hoses	4x operating pressure
Return Filters	10 micron absolute

HYDRAULIC CYLINDER SPECIFICATIONS

Tailgate Cylinders	2.5" x 1.75" x 41.625"
Body Hoist Cylinders	5.5" x 4.5" x 3.5" x 77"

STANDARD EQUIPMENT

- Chrome cylinder rods
- Sight gauge on hydraulic reservoir
- Tailgate ajar alarm
- Imron elite productive paint
- Frame-mounted arm
- Ergonomic in-cab control panel and joystick
- Smooth body sidewall design
- Positive automatic tailgate lock
- Back up alarm
- Hour meter
- "Arm stowed" indicator
- LED lighting system
- ANSI Z 245.1-2008 compliant

OPTIONAL EQUIPMENT

- Camera options
- Additional arm control locations
- Hopper ladder
- Broom/shovel racks
- Street-side semi-automated cart tipper
- Hydraulic drop-down hopper panel
- CNG tank options

† As measured from top of truck frame.

*Any chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted.
(Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)

AUTHORIZED NEW WAY DEALER

SANSOM
Equipment Company



Sourcewell
Formerly NAW
Awarded Contract
Contract # 091219-NWY

NEW WAY® Driving The Difference.®

a quality product of McLaughlin FAMILY COMPANIES • 800 831 1858 • www.newwaytrucks.com

20-1911 REV 06-20