RF 40x40 Roll Label

The RF 40x40mm label delivers dependable performance and merchandise protection using RF technology. The label's small footprint minimizes impact on brand promotion and important product information, allowing application on virtually any package size.

This label is available in two sizes. The small rolls are designed for hand and tabletop application and the large rolls are for automatic application at the point of manufacturing. When applied to merchandise at the point of manufacturing, retailers receive floor-ready merchandise with consistent label placement to expedite receiving and selling floor fulfillment.

Retailer Values

// Provides visual deterrence while minimizing impact on brand promotion and important product information

// Protects merchandise by tagging at the point of manufacturing so merchandise arrives shelf-ready

// Permits open merchandising while still combatting theft

Product Codes

Small Roll:

XL40-DPW2KLU2: White

XL40-DBC2KLU2: Mock Barcode

Large Roll:

XL40-DPW8KLU: White

Technology

RF

Environmental Constraints

Temperature

12°-25°C (54°-77°F)

Humidity

55% maximum

Shelf Life

Small and Large Rolls:

Two years from date of manufacture when labels are stored between 12°-25°C (54°-77°F).

Mode of Application

Small Roll:

Hand or Tabletop

Large Roll:

Automatic

Materials of Construction

Small & Large Rolls

70µm AL+15µm CPP+10µm AL

Hot Melt Adhesive

934E Henkel

Dimensions

Color .... White, Mock Barcode

Length...........................40mm ± 0.5mm
(1.57in ± 0.0197in)

Width ....40mm ± 0.5mm
(1.57in ± 0.0197in)

Thickness................. 0.20mm ± 0.015mm
(0.0078in ± 0.0006in)

Liner Width .... 43mm ± 1.0mm
(1.69in ± 0.0394in)

Label to Liner Spacing

....3.mm ± 0.5mm
(0.12in ± 0.0197)

Note: Warranty terms and conditions are as specified in the applicable Sales Agreement.

tyco *Retail Solutions*

www.sensormatic.com   **/ 1 /**

CE This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both

See Sensormatic.com for Usage Instructions

RF 40x40mm Roll Label

ROLL SPECIFICATIONS

	Small Roll	Large Roll		Small Roll	Large Roll
PRODUCT CODE	XL40-DPW2KLU2 XL40-DBC2KLU2	XL40-DPW8KLU	PRODUCT CODE	XL40-DPW2KLU2 XL40-DBC2KLU2	XL40-DPW8KLU
Diameter Of Core	76mm (2.9) core	76mm (2.9) core	External Carton Dimensions	48 x 21 x 22cm (18.89 x 8.26 x 8.66in)	39 x 39 x 26cm (15.35 x 15.35 x 10.23in)
Max Roll Diameter	185mm (7.28in)	360mm (14.16in)	External Cubic Ft. Per Case	0.78	1.22
Number Splices	10 maximum	10 maximum	Labels per Roll	2,000	8,000
Roll Weight	1.09kg (4.40lbs)	3.89kg (8.582lbs)	Rolls Per Case	10	5
Case Weight (gross)	11.63kg (25.64lbs)	20.45kg (45.06lbs)	Cases Per Pallet	50	30