

Factory item no.	Product name	Photo	Technical Data, material, size etc.	Unit packing	Q'ty in Master Carton	Q'ty in Inner Box	Master Carton Size (cm)	MC G.W./N.W. (kg)	20' Q'ty (pcs)	40' Q'ty (pcs)	Available Certificates
1	XR400 SS		Gross capacity: 368L Net capacity: 357L R600a Energy consumption class: D Stainless steel door Door colour: Stainless steel Temp. range(°C): chiller -2~-+8 Stainless steel handle Lock&key PCM coated cabinet 2 front adjustable feet + 2 back rollers Without internal LED light ABS plastic control panel Standard feet	630*630*1970	1	1	630*630*1970	67/76	27	54	CE, ERP, UKCA
2	XF400 SS		Gross capacity: 325L Net capacity: 304L R290 Energy consumption class: C Single solid door Door colour: white/black Temp. range(°C): freezer -18~-22 Stainless steel handle Lock&key PCM coated cabinet 2 front adjustable feet + 2 back rollers Without internal LED light ABS plastic control panel Standard feet	630*630*1970	1	1	630*630*1970	69/78	27	54	CE, ERP, UKCA
3	XR600-H6C		Gross capacity: 588L Net capacity: 543L R600a Energy consumption class: D Single solid door Door colour: white/black Temp. range(°C): chiller -2~-+8 Grip handle Lock&key PCM coated cabinet 2 front adjustable feet + 2 back rollers Without internal LED light ABS plastic control panel Standard feet	807*740*2010	1	1	807*740*2010	84/98	21	42	CE, ERP, UKCA
4	XF600-HC		Gross capacity: 580L Net capacity: 538L R290 Energy consumption class: B Single solid door Door colour: white/black Temp. range(°C): freezer -18~-22 Grip handle Lock&key PCM coated cabinet 2 front adjustable feet + 2 back rollers Without internal LED light ABS plastic control panel Standard feet	807*740*2010	1	1	807*740*2010	86/100	21	42	CE, ERP, UKCA