



# DIABLO

## 300W PROFILE LUMINAIRE

### OPTICS

- 13-element 8:1 zoom high-resolution optic system
- Beam aperture: 6.7° to 53°
- Fast motorised linear zoom
- Tempered anti-reflective coated lenses
- 119 mm frontal lens for greater performance

### LIGHT SOURCE

#### DIABLO-S

- 26,500 lumen, 8000 K white-light engine
- Total luminaire output: up to 19,000 lumens
- Colour temperature output: 6500 K
- CRI: greater than 70

#### DIABLO-TC

- 20,500 lumen 7000 K white-light engine
- Total luminaire output: up to 14,000 lumens
- Colour temperature output: 5700 K
- CRI: greater than 90

- Rated source life: up to 25,000 hours
- Flicker-free source management suitable for TV applications and all video-recorded events

### MOVEMENT

- Extremely accurate positioning
- Moving-head operated with either 8- or 16-bit resolution
- High-resolution stepper motors operated via microprocessors to ensure extreme accuracy and smooth movement
- Pan and tilt automatic repositioning
- Moving-head range: 540° (pan), 270° (tilt)

### COLOURS

- Sophisticated colour mix system providing CMY colour mixing
- Variable CTO colour temperature correction
- Fixed colour wheel with seven complementary colours

### GOBOS

- Indexable rotating gobo wheel with 7 high-precision glass gobos, plus open position
- Adjustable-speed rotating gobo in both directions
- Gobo diameter: 25.0 mm
- Image diameter: 20.0 mm

### FRAMING SYSTEM

- 4 individually positionable shutter blades
- Rotation of the framing system module: +/- 45°

### IRIS DIAPHRAGM

- Fast iris diaphragm with adjustable dynamic effects
- Iris range: 15% to 100% open

### FROST

- Heavy frost filter
- Light frost filter (optional)

### EFFECTS

- Graphic animation effect-wheel with continuous rotation in both directions
- 5-facet circular indexable rotating prism
- Sparkle effect: dynamic animation effect with speed and fade adjustment

### DIMMER / STROBE

- Electronic dimmer, allowing perfect light adjustment from 0 to 100% without colour variation
- White or colour strobe effect, with speed adjustment from 1 to 25 flashes per second

### SOFTWARE FEATURES

- Local DMX addressing of luminaire and optional parameters through a built-in LCD control panel
- Remote DMX addressing of luminaire and optional parameters through a standard RDM DMX controller
- Information menu including hour counter, temperature, software version

### HARDWARE FEATURES

- Graphic LCD display for addressing and special functions settings, with flip function
- Clicking jog wheel to set functions
- Excess-temperature protection
- Integrated wireless CRMX TiMo™ RDM receiver from LumenRadio™
- XLR 5-pin male and female connectors for DMX connection
- PowerCON TRUE1 male and female connectors for power connection

### CONTROL

- DMX 512 protocol, through DMX cable or a wireless system
- DMX-RDM compatible
- Stand-alone mode and Master/Slave modes
- Local control panel, with LCD display
- Choice of 3 DMX modes (from 36 to 56 DMX channels)

### POWER SUPPLY

- Electronic supply with active PFC
- 100 to 240 Volts – 50/60Hz
- Power: 550 W maximum

### COOLING SYSTEM

- Advanced liquid cooling system
- Self-adjusting variable speed fans for quiet operation (Auto mode)
- Selectable ventilation user modes including a new Silent Mode
- Safety protection against temperatures excesses

### HOUSING

- Moving-head skeleton made of aluminium and steel metal plates
- Base in die-cast aluminium
- Aluminium and copper heatsinks
- Moulded covers in self-extinguishing fire retardant ABS PC (V0 class)
- Two-side handles for transportation
- Four heavy-duty feet for better stability
- IP20 protection rating
- Exterior finish: black (Carbon)

### INSTALLATION

- Fastening-bracket system: two Omega ¼ turn brackets designed for use with standard clamps
- Mounting points: four ¼ turn locking fittings allowing installation of Omega brackets on luminaire
- Safety-cable attachment point

### OPERATING PARAMETERS

- Operating positions: all (device on floor or fixed to a support)
- Maximum permitted ambient temperature (T<sub>a</sub> max): 45° C (113° F)
- Minimum permitted ambient temperature (T<sub>a</sub> min): -10° C (14° F)
- Minimum usage distance: 1.5 m (4.92 ft)

### COMPLIANCE

- EMC Directive 2014/30/EU
- LVD Directive 2014/35/EU

### SIZE

- Product: 365 x 591 x 212 mm (l x h x d)
- Flight-case foam: 430 x 660 x 280 mm (l x h x d)

### WEIGHT

- Product: 21.8 KG

### PRODUCT CODES

- 011340: DIABLO-S PROFILE LUMINAIRE
- 011350: DIABLO-TC PROFILE LUMINAIRE

### LEGAL

- DIABLO is AYRTON registered Trademark
- DIABLO is a patented model