



# 4G Handheld Computer Specification



## Specifications

|                     |                    |   |
|---------------------|--------------------|---|
| Basic configuration | Product Model      | LS-KP36   |
|                     | CPU                | MTK6762, Octa-core 2.0Ghz   |
|                     | OS Version         | Android11.0   |
|                     | Memory             | 4GB RAM+64GB ROM(MTK6762)   |
|                     | Bluetooth          | Bluetooth 5.0   |
| LCM                 | LCD                | 4 inch (IPS), HD+, 800*480  |
|                     | TP                 | Capacitive multi touch screen, Panda glass  |
| Network             | WLAN               | Support 2.4/5GHz dual-band WIFI<br>Support 802.11ac, Wi-Fi 5  |
|                     | Cellular data      | 4G:TDD LTE FDD LTE;<br>3G:HSPA+ ,EVDO, GPRS EDGE;<br>2G:GPRS class 12/EDGE  |
| Sensor              | GNSS               | GPS/Beidou/Galileo/GLONASS/AGPS   |
|                     | Motion Sensor      | 3-axis Accelerometer with MEMS Gyro   |
|                     | Light Sensor       | Automatically adjusts display backlight brightness  |
|                     | NFC                | Support, 13.56MHz<br>Contactless interface modem<br>- ISO/IEC 18000-3、18092<br>- ISO/IEC 14443 A/B<br>- ISO/IEC 15693 Mifare compliance<br>only MTK6762 support |
| Camera              | Front              | 5mp FF  |
|                     | Rear               | 13mp AF   |
|                     | Flashlight         | Support   |
| Audio               | Speaker            | Power: 1.5W 8 Ω BOX   |
|                     | Receiver           | Support   |
|                     | Motor              | Support   |
|                     | MIC                | Dual MIC, 3D DNR MIC  |
| IO interface        | Earphone           | Not support   |
|                     | USB                | Type-C USB2.0+charging, support OTG cable, 5V/2A  |
|                     | SIM Card type      | Dual cards(SIM+SIM or SIM+TF)   |
|                     | TF card slot       | Support TF card(up to 256GB)  |
| Data Capture        | Fingerprint module | Not support   |
|                     | Scan module        | CM60, support 1D/2D code  |
| Others              | Button             | Total 34 Physical keys, front keys*29, side scan keys*2, side keys*1, volume ± keys*2   |
|                     | Google GMS         | Support   |
|                     | Battery            | Removable battery, 5000mAh gel polymer, 4.35V (3.8V), 10K NTC resistance  |
|                     | Dimension          | 165 x 65 x 15mm   |
|                     | Certifications     | 3C certification, Drop test report,RoHS report  |

|             |                       |  |
|-------------|-----------------------|--|
| Accessories | Adaptor PE+           | DC 5V/2A, 9V2A 33W flash charge            |
|             | Cable                 | Type-C USB2.0+charging                     |
|             | Wrist strap           | Optional                                   |
|             | Cradle                | Optional                                   |
| Environment | Operating Temperature | -20°C-60°C                                 |
|             | Storage Temperature   | -40°C-70°C                                 |
|             | Working Humidity      | 5%-95%                                     |
|             | Drop Specifications   | Multiple 1.5 m drops to tile over concrete |
|             | Sealing               | IP65                                       |

Laison Tech (Hong Kong) Limited

12D North District of Zhonghai Xian Huafu, Bao'an District, Shenzhen City,China, 518051

Email: [info@leeshion.com](mailto:info@leeshion.com)

Site: [www.leeshion.com](http://www.leeshion.com)

Copyrights © 2025 Leeshion Corp. All Rights Reserved

\*Product specifications and availability are subject to change without notice