

Safety Data Sheet


according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

1 Identification

- **Product identifier**
- **Trade name:** Rubber Cement
- **Product code:** See section 16 for list of product codes.
- **Recommended use and restriction on use**
- **Recommended use:** Adhesives
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
ITW Global Tire Repair, Inc.
125 Venture Drive, Suite 210, San Luis Obispo, CA 93401
Tel (805) 489-0490
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585(International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS02 GHS07 GHS08
- **Signal word:** Danger
- **Hazard statements:**
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing mist, vapors, or spray.
P264 Wash thoroughly after handling.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 1)







- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

8032-32-4	Ligroine  Flam. Liq. 2, H225  Asp. Tox. 1, H304	40-60%
9003-35-4	Formaldehyde, oligomeric reaction products with phenol  Eye Irrit. 2A, H319; Skin Sens. 1A, H317	10-20%
586-62-9	Terpinolene  Asp. Tox. 1, H304  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317  Flam. Liq. 4, H227	<10%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
 In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Do not pull solidified product away from the skin.
 Immediately wash with water and soap and rinse thoroughly.
 If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn, if possible.

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 2)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed:

Causes eye irritation.

Allergic reactions

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

· Danger:

May be fatal if swallowed and enters airways.

Danger of impaired breathing.

· Indication of any immediate medical attention and special treatment needed:

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

· Extinguishing media**· Suitable extinguishing agents:**

Gaseous extinguishing agents

Carbon dioxide

Fire-extinguishing powder

Foam

Water fog / haze

· For safety reasons unsuitable extinguishing agents:

Water spray

Water stream.

· Special hazards arising from the substance or mixture

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters**· Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

· Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 3)

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

Avoid breathing mist, vapors, or spray.

Open and handle receptacle with care.

Keep out of reach of children.

· **Information about protection against explosions and fires:**

Highly flammable liquid and vapor.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

8032-32-4 Ligoine

REL (USA)

Long-term value: 350 mg/m³

Ceiling limit value: 1800* mg/m³

*15-min

EL (Canada)

reciprocal calculation method - see OHS5.48-12

LMPE (Mexico)

Short-term value: 1800 mg/m³, 400 ppm

Long-term value: 1350 mg/m³, 300 ppm

A3

· **Exposure controls**

· **General protective and hygienic measures:**

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 4)

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.

- **Engineering controls:** Take precautionary measures against static discharge.

- **Breathing equipment:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material: Nitrile

Thickness: ≥4 mil

Breakthrough time: 2 hours

- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No relevant information available.

- **Risk management measures** No relevant information available.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form: Liquid

Color: According to product specification

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Melting point/Melting range:** Not determined.

- **Boiling point/Boiling range:** >35 °C (>95 °F)

- **Flash point:** <23 °C (<73.4 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto-ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 5)

<ul style="list-style-type: none"> · Danger of explosion: 	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
<ul style="list-style-type: none"> · Explosion limits <li style="padding-left: 20px;">Lower: <li style="padding-left: 20px;">Upper: · Oxidizing properties: 	<p>Not determined.</p> <p>Not determined.</p> <p>Non-oxidizing.</p>
<ul style="list-style-type: none"> · Vapor pressure: 	Not determined.
<ul style="list-style-type: none"> · Density: <li style="padding-left: 20px;">Relative density: <li style="padding-left: 20px;">Vapor density: <li style="padding-left: 20px;">Evaporation rate: 	<p>Not determined.</p> <p>Not determined.</p> <p>Not determined.</p>
<ul style="list-style-type: none"> · Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.
<ul style="list-style-type: none"> · Partition coefficient (n-octanol/water): 	Not determined.
<ul style="list-style-type: none"> · Viscosity <li style="padding-left: 20px;">Dynamic: <li style="padding-left: 20px;">Kinematic: · Other information 	<p>Not determined.</p> <p>Not determined.</p> <p>No relevant information available.</p>

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Forms flammable gases / fumes.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Reacts violently with oxidizing agents.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Under fire conditions only:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 6)

- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Causes eye irritation.
- **Sensitization:** Sensitization possible through skin contact.

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity**
Toxic to aquatic life with long lasting effects.

586-62-9 Terpinolene

LC50 0.805 mg/l (zebra fish)

- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 8)

Safety Data Sheet





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 7)

14 Transport information

· UN-Number		
· DOT, ADR/RID/ADN, IMDG, IATA	UN1133	
· UN proper shipping name		
· DOT, IATA	Adhesives	
· ADR/RID/ADN, IMDG	ADHESIVES	
· Transport hazard class(es)		
· DOT		
		
· Class	3	
· Label	3	
· ADR/RID/ADN		
		
· Class	3 (F1)	
· Label	3	
· IMDG, IATA		
		
· Class	3	
· Label	3	
· Packing group		
· DOT, ADR/RID/ADN, IMDG, IATA	II	
· Environmental hazards	Product contains environm entally	hazardous
	substances: Terpinolene	
· Marine pollutant:		
	 Yes	
· Special precautions for user	Warning: Flammable liquids	
· Danger code (Kemler):	33	
· EMS Number:	F-E, <u>S</u> -E	
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.	
· Transport/Additional information:		

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 8)

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· **ADR/RID/ADN**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement
(Cont'd. of page 9)
<p>All ingredients are listed or exempt.</p> <ul style="list-style-type: none"> · Proposition 65 (California)
<ul style="list-style-type: none"> · Chemicals known to cause cancer: <p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · Chemicals known to cause developmental toxicity for females: <p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · Chemicals known to cause developmental toxicity for males: <p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · Chemicals known to cause developmental toxicity: <p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · EPA (Environmental Protection Agency): <p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · IARC (International Agency for Research on Cancer): <p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · Canadian Domestic Substances List (DSL): <p>All ingredients are listed or exempt.</p>

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Product codes:**

1022-A, 1034-A, 1050, 1051-A, 2033, 2040-A, 2510, 20134, 20189, 20197, 20271, 20282, 20290, 20290-1, 20458, 20485, 20464, 21032, 24010SL, 24011, 24016, 24018, 24035, 24041

- **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 OSHA: Occupational Safety & Health Administration
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 4: Flammable liquids – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Skin Sens. 1B: Skin sensitisation – Category 1B
 Asp. Tox. 1: Aspiration hazard – Category 1

- **Sources**

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN:

(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 26, 2019

Trade name: Rubber Cement

(Cont'd. of page 10)

978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com