

according to 1907/2006/EC

Revision: 29 July 2019

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

#### · Trade name: Rubber Cement

• Product code: See section 16 for list of product codes.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### · Application of the substance / the mixture: Adhesive.

· Uses advised against: No further relevant information available.

#### • **1.3 Details of the supplier of the Safety Data Sheet** • **Manufacturer/Supplier:** ITW Global Tire Repair, Europe GmbH Carl-Benz Str. 10, 88696 Owingen, Germany Tel 0049 7551-9200-100

Email: Comments@itwgtr.com

### 1.4 Emergency telephone number:

ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International)

United Kingdom 0845 46 47 (England and Wales) 08454 24 24 24 (Scotland) 0808 808 8000 (Northern Ireland) (24 hours)

### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008				
Flam. Liq. 2	H225	Highly flammable liquid and vapour.		
Eye Irrit. 2	H319	Causes serious eye irritation.		
Skin Sens. 1	H317	May cause an allergic skin reaction.		
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.		
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.		

#### <sup>•</sup> 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. • Hazard pictograms



GHS02 GHS07 GHS08 GHS09

# Signal word Danger Hazard-determining components of labelling: Ligroine Formaldehyde, oligomeric reaction products with phenol Terpinolene

(Cont'd. on page 2)

according to 1907/2006/EC

Revision: 29 July 2019

#### Trade name: Rubber Cement

	(Cont'd. from page 1)
· Hazard st	atements
	nly flammable liquid and vapour.
	ses serious eye irritation.
	cause an allergic skin reaction.
	be fatal if swallowed and enters airways.
	ic to aquatic life with long lasting effects.
· Precautio	nary statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P31	10 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P370+P37	78 In case of fire: Use foam, powder, or carbon dioxide for extinction.
P403+P23	35 Store in a well-ventilated place. Keep cool.
	<b>r hazards</b> There are no other hazards not otherwise classified that have been identified. <b>f PBT and vPvB assessment</b> applicable.

· vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### <sup>•</sup> 3.2 Mixtures

· Components:		
CAS: 8032-32-4 EINECS: 232-453-7 Index number: 649-263-00-9 Reg.nr.: 01-2119474695-24-XXXX	Ligroine Flam. Liq. 2, H225 Asp. Tox. 1, H304	40-60%
CAS: 9003-35-4 NLP: 500-005-4 Reg.nr.: 01-2120735197-51-XXXX	Formaldehyde, oligomeric reaction products with phenol Eye Irrit. 2, H319; Skin Sens. 1A, H317	10-20%
CAS: 586-62-9 EINECS: 209-578-0 Reg.nr.: 01-2119982325-32-XXXX	Terpinolene Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1B, H317	<10%

#### · Additional information:

For the listed ingredient(s), the identity and/or exact percentages are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

#### • After skin contact:

Do not pull solidified product off the skin.

Immediately wash with water and soap and rinse thoroughly.

(Cont'd. on page 3)



according to 1907/2006/EC

Revision: 29 July 2019

### Trade name: Rubber Cement

(Cont'd. from page 2) If skin irritation or rash occurs: Get medical advice/attention. · After eye contact: Remove contact lenses if worn, if possible. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. A person vomiting while lying on their back should be turned onto their side. 4.2 Most important symptoms and effects, both acute and delaved Causes eve irritation. Allergic reactions Gastric or intestinal disorders when ingested. Nausea in case of ingestion. · Hazards: May be fatal if swallowed and enters airways. Danger of impaired breathing. 4.3 Indication of any immediate medical attention and special treatment needed If necessary oxygen respiration treatment. Later observation for pneumonia and pulmonary oedema. **SECTION 5: Firefighting measures** 5.1 Extinguishing media Suitable extinguishing agents: Gaseous extinguishing agents Carbon dioxide Fire-extinguishing powder Foam Water haze or fog · For safety reasons unsuitable extinguishing agents: Water spray Water with full jet 5.2 Special hazards arising from the substance or mixture Highly flammable liquid and vapour. Formation of toxic gases is possible during heating or in case of fire. 5.3 Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Protect from heat.
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
(Cont'd. on page 4)

according to 1907/2006/EC

Revision: 29 July 2019

(Cont'd. from page 3)

#### Trade name: Rubber Cement

#### • 6.2 Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

#### 6.3 Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Send for recovery or disposal in suitable receptacles.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Use only in well ventilated areas. Avoid contact with the eyes and skin. Avoid breathing mist/vapours/spray. Open and handle receptacle with care. Keep out of reach of children. **Information about fire - and explosion protection:** Highly flammable liquid and vapour. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Flammable gas-air mixtures may form in empty receptacles.

## 7.2 Conditions for safe storage, including any incompatibilities

• Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

- Information about storage in one common storage facility:
- Store away from foodstuffs.

Store away from oxidising agents.

• 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

#### <sup>•</sup> 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 8032-32-4 Ligroine

OEL (Ireland) Carc1B, Muta1B

• DNELs: No further relevant information available.

· PNECs: No further relevant information available.

#### <sup>•</sup> 8.2 Exposure controls

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

(Cont'd. on page 5)



according to 1907/2006/EC

Revision: 29 July 2019

#### Trade name: Rubber Cement

(Cont'd. from page 4)

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. • **Respiratory protection:** Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation.

• Protection of hands:

M 2

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material: Nitrile Thickness: ≥4 mil Breakthrough time: 2 hours

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Protective work clothing

• Limitation and supervision of exposure into the environment: No further relevant information available.

• **Risk management measures:** No further relevant information available.

SECTION 9: Physical and chemical properties				
9.1 Information on basic physical	and chemical properties			
Appearance				
Form:	Liquid			
Colour:	According to product specification			
· Odour:	Characteristic			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
• Melting point/freezing point:	Not determined.			
Initial boiling point and boiling range	: >35 °C			
· Flash point:	<23 °C			
· Flammability (solid, gas):	Not applicable.			
· Auto/Self-ignition temperature:	Not determined.			
· Decomposition temperature:	Not determined.			
· Explosive properties:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.			
· Explosion limits				
Lower:	Not determined.			
Upper:	Not determined.			
	(Cont'd. on page			





according to 1907/2006/EC

Revision: 29 July 2019

#### Trade name: Rubber Cement

		(Cont'd. from page
· Oxidising properties	Non-oxidising.	
· Vapour pressure:	Not determined.	
· Density:		
Relative density:	Not determined.	
Vapour density:	Not determined.	
Evaporation rate:	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/	water: Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
<sup>•</sup> 9.2 Other information	No further relevant information available.	

### **SECTION 10: Stability and reactivity**

. 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

#### 10.3 Possibility of hazardous reactions

Highly flammable liquid and vapour.

Forms flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Reacts violently with oxidising agents.

Toxic fumes may be released if heated above the decomposition point.

· 10.4 Conditions to avoid Excessive heat.

· 10.5 Incompatible materials Oxidisers

### 10.6 Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

• Acute toxicity: Based on available data, the classification criteria are not met.

- · LD/LC50 values relevant for classification: None.
- · Primary irritant effect

• Skin corrosion/irritation: Based on available data, the classification criteria are not met.

· Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

(Cont'd. on page 7)



according to 1907/2006/EC

Revision: 29 July 2019

#### Trade name: Rubber Cement

(Cont'd. from page 6)

#### · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

#### · Probable routes of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· Germ cell mutagenicity: Based on available data, the classification criteria are not met.

• Carcinogenicity: Based on available data, the classification criteria are not met.

• **Reproductive toxicity:** Based on available data, the classification criteria are not met.

• **STOT-single exposure:** May cause drowsiness or dizziness.

• STOT-repeated exposure: Based on available data, the classification criteria are not met.

• Aspiration hazard:

May be fatal if swallowed and enters airways.

## **SECTION 12: Ecological information**

#### <sup>·</sup> 12.1 Toxicity

· Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

586-62-9 Terpinolene

#### LC50 0,805 mg/l (zebra fish)

• **12.2 Persistence and degradability** No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

**vPvB:** Not applicable.

\* **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### · Recommendation

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

#### · Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

(Cont'd. on page 8)



according to 1907/2006/EC

Revision: 29 July 2019


Trade name: Rubber Cement (Cont'd. from page 7) <sup>•</sup> 14.1 UN-Number · DOT, ADR/RID/ADN, IMDG, IATA UN1133 14.2 UN proper shipping name · DOT, IATA Adhesives · ADR/RID/ADN, IMDG **ADHESIVES** 14.3 Transport hazard class(es) · DOT · Class 3 · Label 3 · ADR/RID/ADN · Class 3 (F1) · Label 3 · IMDG, IATA · Class 3 · Label 3 14.4 Packing group DOT, ADR/RID/ADN, IMDG, IATA Ш 14.5 Environmental hazards: Product contains environmentally hazardous substances: Terpinolene • Marine pollutant: Yes 14.6 Special precautions for user Warning: Flammable liquids. Danger code (Kemler): 33 · EMS Number: F-E,S-E 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · DOT (Cont'd. on page 9)



according to 1907/2006/EC

Revision: 29 July 2019

(Cont'd. on page 10)



## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients are listed.

· Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



according to 1907/2006/EC

Revision: 29 July 2019

#### Trade name: Rubber Cement

(Cont'd. from page 9)

#### **SECTION 16: Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Product codes: 1022-A, 1034-A, 1050, 1051-A, 2033, 2040-A, 2510, 20134, 20189, 20197, 20271, 20282, 20290, 20458, 20464, 21032, 24010SL, 24011, 24016, 24018, 24035, 24041 Relevant phrases H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. Abbreviations and acronyms: ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (RÈACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Skin Sens. 1B: Skin sensitisation - Category 1B Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com