

Attach manufacturer documentation of filter efficiency.

EMISSIONS INVENTORY INFORMATION For Inventory Year – 2024

FORM 3: INDUSTRIAL PAINT AND SOLVENT USE

Facility ID	Facility Name	Facility Name			Contact					
List paints and all solvents used for cleanup and thinning for commercial, industrial, and institutional coating operations and applications. Please list acetone separately. Find the VOC content of the materials from the MSDS or your paint supplier. Calculate emissions. Be sure to use the correct units of measure. Please fill in each column and retain a copy for your records. Formula: (Amt Used - Amt Waste) X VOC Content of each coating = VOCs Emitted										
Type of Coatin	ng or Solvent	Amount Used (gal/yr)	Amount to Waste ¹ (gal/yr)	Co	VOC enten (lb/gal)	t	VOCs Emitted (lb/yr)	Chromates ² (yes/no)		
Page Subtotal VOCs Emitted ³ Page of							lb/year			
Estimated numb	OCs Emitted ³ Grand Total VOCs / Days					lb/year Estimated lb/day				
(1) Attach a summary (2) Indicate whether (3) Report Total VOC	each product contair	ns chromates (c				d.				
Do you use a bo	oth in your coatir	ng operation?	Yes		No		_			
If yes, please provide the filter efficiency of your filters %										
Continue on anoth Include MSDS data		•								