

EMISSIONS INVENTORY INFORMATION For Inventory Year - 2018

FORM 17: PETROLEUM REFINING PROCESS

Facility ID	Facility Name	Contact	
Total Refinery Fe	eed (bbl/yr x 10³):		
Sulfur in Feed (%) ⁽¹⁾ :	_	
Oily Water Treat	ment System:		
VOC conte	nt (ppm) ⁽¹⁾ :		
Total waste	ewater treated (mmgal):		
VOC Emiss	ions:		
Average of of the was	ter of 2-26-91): 365 days x 11.9 kg/d x 3 quarterly determinations of chemical of tewater (kg COD/m ³): mponent removed as sludge (kg/yr):		4.80 tons per year
_	quarterly determinations of nitrogen i	n effluent (kg	
Cooling Towers:			
Highest an	nual cooling tower hydrocarbon (ppm)	(1).	
Total water through cooling towers (mmgal/hour):			(A)
Emfac from AP-42, Table 5.1-2, 5 th ed.: 0.70 lb/mmgal x 8760 hr/yr/2000:			3.066 tpy/mmgal/hr
VOC Emiss	ions (tons/year): (A) x 3.066 tpy/mmga	l/hour:	
Sulfur Recovery:			
Hours tail g	gas unit (B702) was not in service:		(B)
Average flow rate to the absorber in scf/hour, (FQI-1721):			(C)
Average H ₂ S content in vol %, (AI-1704):			(D)
Average TRS as H_2S in TGU in ppm, (Al-1709):			(E)
Estimated	SO_2 emissions from $B702$ in tons per ye	ear:	
[(8]	760 - B) x C x E x 0.1688]/(2000 x 10 ⁶)	_	
SO ₂ emissi	ons from the B602A/B in tons per year:	B602A	
		B602B	

(1) Include recent analytical data supporting this value. **This form is incomplete without this data.**