



**POLY STUDIO FOCUS ROOM KIT
FOR MICROSOFT TEAMS ROOMS
ON WINDOWS**

**POLY STUDIO SMALL/MEDIUM
ROOM KIT FOR MICROSOFT
TEAMS ROOMS ON WINDOWS**

**POLY STUDIO LARGE ROOM KIT
FOR MICROSOFT TEAMS ROOMS
ON WINDOWS**

COMPONENT	<ul style="list-style-type: none"> Poly Focus Room Kit Poly PC for Microsoft Teams Rooms (Dell or Lenovo) 	<ul style="list-style-type: none"> Poly Small-Medium Kit Poly PC for Microsoft Teams Rooms (Dell or Lenovo) 	<ul style="list-style-type: none"> Poly Large Room Kit Poly PC for Microsoft Teams Rooms (Dell or Lenovo)
ROOM SIZE	<ul style="list-style-type: none"> Focus Rooms 10x10 ft (3 x 3m) 1-2 people 	<ul style="list-style-type: none"> Small to medium-sized conference rooms Up to 15 x 20 ft (4.5 x 6m) 	<ul style="list-style-type: none"> Large conference rooms and multi-purpose spaces 15 x 28 ft (4.5 x 8.5m)
TOUCH CONTROLLER	<ul style="list-style-type: none"> Poly GC8 	<ul style="list-style-type: none"> Poly GC8 	<ul style="list-style-type: none"> Poly GC8
COMPUTE APPLIANCE	<ul style="list-style-type: none"> Dell Optiplex 7080 XE (Intel i5 10th generation, 8GB RAM, 128GB SSD) Lenovo ThinkSmart Core (Intel i5 11th generation, 8GB RAM, 256GB SSD) Lenovo ThinkSmart Edition Tiny* 	<ul style="list-style-type: none"> Dell Optiplex 7080 XE (Intel i5 10th generation, 8GB RAM, 128GB SSD) Lenovo ThinkSmart Core (Intel i5 11th generation, 8GB RAM, 256GB SSD) Lenovo ThinkSmart Edition Tiny* 	<ul style="list-style-type: none"> Dell Optiplex 7080 XE (Intel i5 10th generation, 8GB RAM, 128GB SSD) Lenovo ThinkSmart Core (Intel i5 11th generation, 8GB RAM, 256GB SSD) Lenovo ThinkSmart Edition Tiny*
CONFERENCE CAMERA	<ul style="list-style-type: none"> Poly Studio P15 	<ul style="list-style-type: none"> Poly Studio 	<ul style="list-style-type: none"> Poly Studio E70
CAMERA SPECIFICATIONS	<ul style="list-style-type: none"> 90° DFOV UHD 2160p (4K) capture resolution 4x Zoom/EPTZ Auto-Framing 	<ul style="list-style-type: none"> 120° DFOV UHD 2160p (4K) capture resolution Electronic Zoom up to 5x zoom/EPTZ Automatic group framing and speaker tracking 	<ul style="list-style-type: none"> 2 lenses: 120° DFOV and 70° DFOV UHD 2160p (4K) capture resolution 10x digital zoom Automatic group framing and speaker tracking
AUDIO	<ul style="list-style-type: none"> Poly Studio P15 integrated mono speaker Poly NoiseBlockAI technology Poly Acoustic Fence technology 	<ul style="list-style-type: none"> Poly Studio integrated stereo speakers Poly NoiseBlockAI technology Poly Acoustic Fence technology 	<ul style="list-style-type: none"> Not included. Add a certified USB audio or DSP
MICROPHONE	<ul style="list-style-type: none"> 3-element beamforming microphone array 	<ul style="list-style-type: none"> 6-element beamforming microphone array 15 ft/ 4.5 m (Optional expansion microphone available) 	<ul style="list-style-type: none"> Add a certified USB audio or DSP
OTHERS	<ul style="list-style-type: none"> 10 m fiber optic USB cable 	<ul style="list-style-type: none"> 10 m fiber optic USB cable 	<ul style="list-style-type: none"> 10 m fiber optic USB cable
WARRANTY	<ul style="list-style-type: none"> 1-year warranty, parts and labor Poly+ Service available for premium support features 	<ul style="list-style-type: none"> 1-year warranty, parts and labor Poly+ Service available for premium support features 	<ul style="list-style-type: none"> 1-year warranty, parts and labor Poly+ Service available for premium support features

*Availability limited to certain countries



POLY TC8



SPECIFICATIONS

PACKAGE INCLUDES:

- Poly TC8 and RJ45 (LAN) cable
- Setup sheet
- Printed warranty statement

PHYSICAL CHARACTERISTICS

- Physical dimensions: 205 W x 123 H x 79 D mm [8.07" W x 4.84" H x 3.11" D in]
- Micro-B USB 2.0 (diagnostics)
- Mechanical locking mechanism (Kensington lock)
- Weight: 812 g (1.79 lb)

OPERATING ENVIRONMENT

- Temperature: 0 to 40 °C (32 - 104 °F)
- Non-operating: -20 to 60 °C (-20 - 140 °F)

ALTITUDE

- Operating: 0 to 10,000 ft ASL
- Non-operating: 0 to 35000 ft ASL

COMPATIBLE SYSTEMS

- Poly G7500 (min 3.0 software)
- Poly Studio X30 and Studio X50

USABILITY

- Display: 8-inch screen
- Aspect ratio: 16 x 10
- Resolution: WXGA (1280 x 800)
- Designed with built-in stand support—no external stand required

- Viewing angle: 75 degrees (U/D/L/R)
- Positioning/placing angle: 60 degrees
- Tap and touch control to access call controls and administrative menus
- Intuitive user interface

TECHNOLOGY

- Capacitive touch sensor supports multi-touch functionality
- Direct API command through network
- LCD panel with LED backlighting
- IPS (In-Plane Switching)
- Ultra Sonic Emitter (for auto pairing)

ELECTRICAL

- Power over Ethernet (PoE), compatible with IEEE 802.3af Class 3
- Low-power sleep mode

WARRANTY

- One-year return to factory parts and labor
- 90-day software warranty

PART NUMBER

- 2200-30760-001