




TM.ONTEC R C1 60 NM AT

TM-OR.C1ATN600W




PARAMETERS

Standards	PN-EN 60598-1, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838
Warranty	24 months - AT 36 months - ST 60 months - DATA, CB
Application	escape route lighting
IP	IP20
IK	IK03
Version	AT - auto-test / self-test
Power supply	210+250 V AC 50+60 Hz
Power supply CB	186+254 V DC
Temperature range	10-35 °C
Material	PC
Colour	RAL9003
Duration time	1 h
Operating mode	NM
Maximum light power (the luminaire can power the light source with a different power)	2 W
Active power	1.2 W
Insulation class	2
Luminous flux	306 lm
Battery	LiFePO4/C 3.2V 1.5Ah
Dimming mode	no



PHOTOMETRY [m]



Ceiling height

2,5
3,0
4,0
5,0
6,0
7,0
8,0
9,0
10,0

Distance wall - fitting

8,7
9,8
11,4
12,0
4,9
3,6
3,2

Distance fitting - fitting

19,4
22,2
26,7
30,5
28,7
22,4
18,6

