

RACE	
TRACK	
NAME	
CITY / COUNTRY	
DATE	

TEMPERATURE	AIR	TRACK	
QUALIFYING POSITION	BEST LAP TIME	FINAL POSITION	
	SEC	MIN	
TRACK CONDITION	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

GEAR RATIO CHART

Spur Pinion	56	57	58	60	61	62
22	6.11	6.22	6.33	6.55	6.65	6.76
23	5.84	5.95	6.05	6.26	6.37	6.47
24	5.60	5.70	5.80	6.00	6.10	6.20
25	5.38	5.47	5.57	5.76	5.86	5.95
26	5.17	5.26	5.35	5.54	5.63	5.72
27	4.98	5.07	5.16	5.33	5.42	5.51
28	4.80	4.89	4.97	5.14	5.23	5.31
29	4.63	4.72	4.80	4.97	5.05	5.13
30	4.48	4.56	4.64	4.80	4.88	4.96

Front	SHOCK		Rear
OIL	SHOCK PISTON	OIL	
CST	HOLE SIZE	CST	
SPRING	F mm	SPRING	
	R mm		

Front	TIRE		Rear
Front Left	Tire Shore	Rear Left	
Front Right		Rear Right	
Front Left	Tire Ø	Rear Left	
Front Right		Rear Right	
	Tire Additive		

BODY

Bumper	BODY MOUNT DISTANCE
Standard	mm
Cut	
BODY	WING
	mm

NOTE

WHEEL BASE	BUMP STEER	CASTER
mm	mm	mm
TOWER POSITION	FRONT ARM	
mm	☐ S ☐ M ☐ H	

STEERING BLOCK SETUP					
CENTER R806021	CENTER	BACKWARD	FORWARD	LOWER	UPPER

REAR UPRIGHTSHIMS	mm

ECCENTER HUB		
☐ Up	☐ Middle	☐ R806021
REAR ARM	☐ S ☐ M ☐ H	

FRONT

RIDE HEIGHT	FRONT UPPER ARM
mm	☐ ☐ ☐
WHEEL SHIMS	CAMBER
mm	R °
	L °

REAR

1 HOLE	RIDE HEIGHT
	mm
2 HOLES INSIDE	2 HOLES OUTSIDE
WHEEL SHIMS	CAMBER
mm	R °
	L °

DOWN STOP	FRONT LOW ARM	REAR ROLL CENTER	I-TYPE	REAR UPPER LINK	DOWN STOP
mm	☐ ☐ ☐	☐ ☐	☐ ☐	☐ ☐ ☐	mm

REAR TOE	FRONT TOE
IN °	OUT °
	IN °
FRONT ANTI-ROLL BAR	ACKERMAN
mm	☐ 10mm ☐ 9mm ☐ 8.5mm
REAR ANTI-ROLL BAR	STIFFENER
mm	REMOVED
	R828004
TRACK WIDTH	TRACK WIDTH
mm	mm