Inferno MP10Te *SET UP SHEET*

KYOSHO ® THE FINEST RADIO CONTROL MODELS

ver.1.00

Driver	Date	Track	Event	Spur Gear	Pinion Gear
				☐ 45T ☐ 46T ☐ 47T ☐ 48T	T
		Condition :			

Motor	Battery	ESC	Tires	Tire Insert	Wheel	Body
			Compound :			

● Diff. Gear Set-Up

	Front	Center	Rear
	☐10/20 ☐12/18 ☐LSD	☐10/20 ☐12/18 ☐LSD	☐10/20 ☐12/18 ☐LSD
Diff. Gear	#	Diff. Size ☐ Small ☐ Large #	#

● Shock Set-Up

		Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	Size _ type	Size _ type
Shock Piston	B : Black W : White T : Taper	φ x	φ x
Shock Oil		#	#
Shock Spring			

● Ride Height

Front	Rear
mm	mm

Front   Rear
Rebound

● Rebound

Front	Rear
mm	mm

● Camber Angle

Front	Rear
+ ° −	+ ° −

Upper Rod

	Front	Rear
	mm	mm

● Toe Angle

Front	Rear
+ ° −	☐ 2.5° ☐ 3° ☐ 3.5°

< Front >

____ mm

● Wheelbase

Collar of Rear Hub	Front Side _____ mm
	Rear Side _____ mm

● Shock Mount Position

<Front>   <Rear>

Sus. Arm

Front	☐ In ☐ Medium ☐ Out
Rear	☐ In ☐ Medium ☐ Out

Shock Stay

Front	☐ Alu ☐ Carbon
Rear	☐ Alu ☐ Carbon

Shock Bush

Front	☐ Short ☐ Std.
Rear	☐ Short ☐ Std. ☐ Long

● Rear Upper Arm Position

☐ Plastic
☐ Aluminum

Hub Carrier Bush
☐ Plastic
☐ Brass

● Front Sus. Arm

☐ Soft (Std.)   ☐ Hard

● Front Sus. Bush

Rear Side	☐ ⬭ ☐ ⬭

● Front Upper Arm Position

● Front Hub Carrier

☐ Plastic   ☐ Aluminum
☐ 13°   ☐ 16°   ☐ 17.5°
☐ 19°   ☐ 22°

Lower Bush	☐ Plastic ☐ Brass

☐ -1° ◯   ☐ 0° ◯   ☐ +1° ◯

● Rear Sus. Bush

Front Side	☐ ⬭ ☐ ⬭ ☐ ⬭ ☐ ⬭
Rear Side	☐ 2.5 2.5 ☐ 3 3 ☐ 3.5 3.5
	☐ 2.5 2.5 ☐ 3 3 ☐ 3.5 3.5

● Rear Sus. Arm

☐ Soft (Std.)   ☐ Hard

Rear Sus. Bush	
☐ Short ◯	
☐ Medium ◯	
☐ Long ◯	

● Steering Plate

Front

● Servo Horn

☐ Plastic   ☐ AL. Long
☐ AL. Short

● Sway Bar

Front	Rear
φ	φ
mm	mm

● Weight

Front	Rear
☐ None	☐ None
☐ IFW604-10	☐ IFW605-10
☐ IFW604-20	☐ IFW605-20
☐ other	☐ other
_____	_____

● Wing

☐ IF491(TKI4)   Flap ☐ None
☐ 5mm
☐ 8mm
☐ Holes

memo :