## KI2 SETUP SHEET KVOZHO ver.1.00 Driver Date Track Event Spur Gear Pinion Gear □45T □ 46T ☐ 47T ☐ 48T Τ Motor Battery ESC Tire Insert Wheel Body Compound Diff. Gear Set-Up Front Sus. Arm Front Hub Carrier ☐ Plastic ☐ Aluminum Center Rear SS Soft (Std.) Hard ☐ 13° ☐ 16° ☐ 17.5° ☐ 19° ☐ 22° \_\_\_\_10/20 \_\_\_ 12/18 \_\_\_LSD | \_\_\_\_10/20 \_\_\_ 12/18 \_\_\_LSD 10/20 12/18 LSD Ring Gear Ring Gear Diff. Size Diff. Gear Front Sus. Bush 43/13 Small Large 42/12 # 42/12 # Rear Side 99 Shock Set-Up Front Upper Arm Position Front Rear Size type Size type P : w/Diaphragm A : Aeration Shock Type B : Black W : White Shock Piston φ Х Х Tape Shock Oil # ☐ Plastic ☐ Brass Front Wheel Hub Lower Bush **Shock Spring** -1° (°) 0°(0) +1° () □ Narrow □ Std. □ Wide Ride Height Front Rear Front Rear Rear Sus. Bush mm mm Front Side Rebound Rebound (3)(33) (33) Front Rear Rear Side (19) (E) mm mm Camber Angle Servo Horn Rear Sus. Arm OI Front Rear Soft (Std.) Hard Steering Throttle Rear Sus. Bush Front Rear Plastic Plastic mm mm AL. Long AL. Short $\bigcirc$ Toe Angle AL. Short Medium (O) < Front > Front Rear Long (0)☐ 2.5° ☐ 3° 3.5° Sway Bar Steering Plate Wheelbase Front Front Side mm Collar of Rear Hub Rear Side mm mm Front Rear Shock Mount Position φ Φ Shock Stay <Front> <Rear> mm $\mathsf{mm}$ Short Long Front Carbon Alu Wing Weight 99Q Short Long Rear Front Rear Alu ☐ IF491(TKI4) Carbon Flap None 5mm Shock Bush None None Sus. Arm 8mm IFW604-10 ☐ IFW605-10 ☐ Short ☐ Std. Front \_\_ In Out Front ☐ In Short Std. Long FW604-20 IFW605-20 Holes Rear Out other other Rear Upper Arm Position Plastic Aluminum **Hub Carrier Bush** Plastic Brass Rear Wheel Hub $(\circ)$ $(\circ)$ □ Narrow □ Std. ☐ Wide $(\circ)$ $\bigcirc$