

RACE: **BASIC SET-UP**
 TRACK: **CARPET**
 NAME: **XRAY FACTORY** DATE: _____

LAPS: _____ BEST LAP TIME: _____ sec
 QUALIFYING POSITION: _____ FINAL POSITION: _____

TRACK

SIZE: OPEN MEDIUM TIGHT

TRACTION: VERY-LOW MEDIUM VERY-HIGH

SURFACE: SMOOTH MEDIUM BUMPY

TYPE: CLAY CARPET ASTRO

CONDITION: BLUE GROOVE HARD PACKED DRY
 DUSTY LOAMY WET

DIFFERENTIAL TYPE

FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 10K cst	OIL _____ cst	OIL 10K cst

SATELLITE GEARS

FRONT	MIDDLE	REAR
COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>
STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING

ONE-WAY TIGHTNESS: _____

SLIPPING ADJUSTMENT: **13** mm

LOOSE 1 CW TURN (BASIC SETUP) FULLY TIGHTEN

GEARING

PINION: _____ T **81** T CENTER DIFF SPUR

FRONT	SHOCKS	REAR
42mm - 4 DOTS	SPRINGS	57mm - 3 DOTS
cst 700	OIL	cst 550
% 0	REBOUND	% 0
<input checked="" type="checkbox"/> 2 HOLES <input type="checkbox"/>	PISTONS	<input checked="" type="checkbox"/> 2 HOLES <input type="checkbox"/>
<input type="checkbox"/> 3 HOLES <input type="checkbox"/>	<input type="checkbox"/> ø1.2mm <input type="checkbox"/>	<input type="checkbox"/> 3 HOLES <input type="checkbox"/>
<input type="checkbox"/> 6 HOLES <input type="checkbox"/>	<input type="checkbox"/> ø1.3mm <input type="checkbox"/>	<input type="checkbox"/> 6 HOLES <input type="checkbox"/>
HOLES <input type="checkbox"/>	<input checked="" type="checkbox"/> ø1.6mm <input type="checkbox"/>	HOLES <input type="checkbox"/>
	<input type="checkbox"/> ø1.4mm <input type="checkbox"/>	
	<input type="checkbox"/> ø1.7mm <input checked="" type="checkbox"/>	
	CUSTOM PISTONS	
	_____ mm _____ mm	

ANTI ROLL BAR

FRONT	THICKNESS	REAR
1.8 mm		1.8 mm

TIRES

FRONT	REAR
BRAND	
COMPOUND	
INSERTS	
XRAY	XRAY
WHEELS	

ELECTRONICS

MOTOR: _____ SPEEDO: _____
 MOTOR TIMING: _____ BATTERY: _____

BATTERY SIZE: STD. SHORT LOW SHORT

BODY

TYPE: **XRAY DELTA 4C** STANDARD LIGHT

COMMENTS

