

SO 2.0

SETTING SHEET Ver.01

CIRCUIT

- INDOOR OUTDOOR
 DIRT ASTROTURF CARPET GLASS WOOD
 WET DRY DUSTY SMOOTH BUMPY
 HARD PACKED CLAY BIUE GROOVE _____
 LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER _____

DATE _____

FRONT

Z2-017GA (DTM3.1)
 Z2-017-3A (S01.0/2.0)

Plastic
 Aluminum

Wide Narrow
 Plastic
 Aluminum

Standard (Z2-008F3A)
 Graphite (Z2-008F3GA)

+1 ↑ Plastic
 0 ↑ Aluminum
 Steel

Graphite
 Hard

0°
 2.5°
 5°

A/B -A/B-
 A/B -A/B-
 Wide Narrow

Wide (S02.0)
 Wide
 Narrow

CAMBER ← → _____ °
 TOE IN OUT _____ °
 RIDE HEIGHT _____ mm

SPRING
 Dot _____

 OIL
 # _____
 φ1.6x2/2.0

 _____ mm X
 _____ mm X

REAR

Plastic
 Z2-30RUMWA (Aluminum)

L5 Standard Graphite
 Plastic
 Z2-415RS2A (Aluminum)

Standard (S01.0/2.0)
 High mount (DTM3.1)

RF 05 01
 RR 05 01

4.3
 5.0
 6.0

S M L
 0.5
 1
 1.5

CAMBER ← → _____ °
 RIDE HEIGHT _____ mm

SPRING
 Dot _____

 OIL
 # _____
 φ1.7x2/2.0

 _____ mm X
 _____ mm X

DRIVE

OLD LCL
 03
 02
 01
 00

4-gear
 2-gear
 # _____

MOTOR → _____ Rotor _____ mm
 GEAR → Spur T / Pinion T : 2.6
 BATTERY → _____
 ESC YOKOMO RPX3 YOKOMO BL-PRO4

Main chassis
 Steel
 Aluminum

OS02.0
 OS01.0
 ODTM3.1
 OCAL3.1

YT-RWS10A
 YT-RW25A

Steel
 Aluminum

TIRE

FRONT
 TIRE → _____
 INSERTS → _____
 WHEELS → _____

REAR
 TIRE → _____
 INSERTS → _____
 WHEELS → _____

OTHER

Z2-DTM31WA (Aero Hi-clearance 7')
 Z2-CAL2WA (LMR27)

COMMENT