		y set	r UP S	SHEE	T		ver	.1.02	KYUSH
Name of Driver	Date Track		ack	Engine		Plug			Muffler
		Condition:							
Spur Gear Clutch Bell Std. LW	Clutch Spring 0.90 1.00 0.95 1.10	Clutch Shoe CarbonX Aluminum _X	Tire Tire: Compounds:	Tire	Insert	Wheel	Вос	dy	Fuel
Diff. Gear Set-Up	0.001.10	Aluminum _X	1	—— ∣ ont Sus. Arm	<u> </u>		● Front	Hub (arrior
Front	Center	Rear	:	Soft (Std.)	'	rd	☐ Plas		Aluminum
10/2012/18LSD	10/2012/18LSI		LSD			Iu	☐ 13°	☐ 16°	☐ 17.5° ☐
Diff. Gear Ring Gear Ring Gear 43/13 42/12 # # # 42/12 #				Front Sus. Bush				77	
Shock Set-Up	#	42/12 #	;	ear Side				(22)	
V Orlook Get-Op	Front	Rear	Fr	ont Upper Ar	m Positi	on			
Shock Type P: w/Diaphragm A: Aeration Size type Size type			De I						
Shock Piston B : Black W : White T : Taper	φ x	φ χ]			
Shock Oil	#	#			/				/
Shock Spring			Fre	ont Wheel H	ub		er Bush		stic Bras
Ride Height	Front		Rear	Narrow 🗌 St	d. Wi	de	1° 🔘 🗆]0°(<u> </u>)
Front Rear	<u> </u>		 	ear Sus. Bus	h				
mm mm				Front Side				3	
Rebound									
Front Rear			!	Rear Side					
mm mm			<u>+,</u>						
Camber Angle			Re	ear Sus. Arm			Servo I	Horn	
Front Rear	+ Positive Camber			Soft (Std.)	☐ Haı	⁻ d	Steerir	ng	Throttle
_	- Negative Camber			Rear Sus	. Bush		☐ Plasti		☐ Plasti
Toe Angle	< Front :	, + <u>+</u> +	- /	Short O Medium O			AL. L	-	∟ AL.
Front Rear			7)	Long 🔘					
° 2.5° 3°	3.5°			eering Plate			● Sway B	Bar	
Wheelbase	<u> </u>				Front	_	 	Д П	
Collar of Rear Hub Front Side	mm			11 } } }	` 				
Rear Side	mm	mm		選り一)	_0.8		Front		Rear
Shock Mount Position	Shock Stay						P		φ
<front> <rear></rear></front>	Front Rear	Short Long Short Long				L		mm	ı
	Rear Upper Sh	nock Bush	· · · · · · · · · · · · · · · · · · ·	eight Front	Rear		/ing		
(999)	Sus. Arm	ong		None None	None		☐ IF491(Th	KI4)	Flap 🗌 Noı 📗 5m
_//	Front [☐ In ☐ Out☐ Out☐ Out☐ Out☐] IFW604-10	☐ IFW60				☐ 8m
Rear Upper Arm Position	Near L] IFW604-20] other	☐ IFW60	JO-20 	0	· ·	☐ Hol
	☐ Plastic	1					Ů		
	Aluminum		me	emo:					
	Hub Carrier B	ush							
	☐ Plastic ☐ Brass								
_	L								
Rear Wheel Hub									