

<b>DRIVER</b>	Kit Std. Setup EU Carpet Alu		
<b>DATE</b>			
<b>TRACK</b>	Carpet Asphalt <input type="radio"/>	RCL Heilbronn	
<b>TRACTION</b>	<input type="radio"/> LOW	<input checked="" type="radio"/> MEDIUM	<input type="radio"/> HIGH
<b>LAYOUT</b>	<input checked="" type="radio"/> SLOW	<input type="radio"/> MIXED	<input type="radio"/> FAST
<b>TEMP °C</b>	<b>AIR</b>	<b>TRACK</b>	
<b>ELECTRONICS</b>			
ESC	ESC SET	MOTOR	
SERVO	RECEIVER	BATTERY	
<b>TIRES</b>			
<b>BRAND</b>	Volante		
<b>TYPE</b>	28		
<b>ADDITIVE</b>	MR33V4		
<b>WARMER °C</b>	FRONT	REAR	
<b>TIME(min)</b>	FRONT 10min	REAR 10min	
<b>SHOCK ABSORBERS</b>			
<b>PISTON</b>	FRONT Kit	REAR Kit	
<b>SHOCK CASE</b>	Kit		
<b>OIL</b>	400	400	
<b>SPRING</b>	6.75	6.5	
<b>LENGTH</b>	10	10	
<b>ANTI ROLL BAR DIAMETER FRONT/REAR</b>			
<b>FRONT</b>	1.1	<b>REAR</b>	1.1
<b>REAR DIFFERENTIAL</b>			
<b>DIFF OIL CST (1,6g oil qty.)</b>	6,000		
<b>GEAR RATIO</b> (T)Spur/(T)Pinion*1,9=Ratio			
<b>PINION</b>		<b>SPUR</b>	
<b>AERODYNAMIC SETTINGS</b>			
<b>BODY TYPE</b>	Twister		
<b>WING TYPE</b>	Twister		
<b>WING POS</b>	(mm)	Neutral	
<b>BODY POSITION</b> (see picture below)	(mm)	52.5	
<b>FRONT BODY HEIGHT &amp; POSITION</b>	<b>REAR BODY POST A2407C</b>	<input checked="" type="radio"/> <b>REAR BODY POST A2416B</b>	<input type="radio"/>
(mm) vertical	47	(mm)	48

**STEERING LIMITER**

A2304 (5mm)

A2305 (5.5mm)

A2306 (6mm)

**STEERING ANGLE IN°**

ap.25

**STEERING ANGLE OUT°**

16

**A2421 USED**

YES

NO

**A2421 SHIM(mm)**

0

**UPPER ARM POS. FR(mm)**

1.5

**FF(mm)**

1.5

**LOWER ARM POS. FR(mm)**

1

**FF(mm)**

1

**SHOCK POS (mm)**

3

**STEERING ROD POS (mm)**

2

**SHIM UPRIGHT L (mm)**

0.5

**UPPERARM POS. (CASTER)**

REAR/5°  FRONT/4°

**SHIM UPRIGHT T(mm)**

2

**CAMBER/°**

2

**TOE OUT/°**

1.25

**OFFSET (mm)**

4

**RIDE HEIGHT(mm)**

5.1

**DOWNSTOP(mm)**

6

**FRONT**

**A2529 POSITION**

INSIDE

OUTSIDE

**A2530 POSITION**

INSIDE

OUTSIDE

**ACKERMANN SHIM (mm)**

1

**SHIM S HORN (mm)**

6

**LENGTH S HORN (mm)**

18.5

**TYPE SERVO HORN**

**REAR TOE ROD POS**

FRONT  REAR

**UPPERARM POS. (CASTER)**

FRONT/-4°  REAR/-3°

**SHIM UPRIGHT T (mm)**

2

**CAMBER/°**

2

**TOE IN/°**

2.75

**OFFSET (mm)**

4.5

**RIDE HEIGHT(mm)**

5.3

**DOWNSTOP(mm)**

4

**REAR**

**WEIGHT(g)**

**BATTERY POSITION FRONT**  **REAR**

**CHASSIS TYPE**

A2415

**MM SCREW**

H2412 (18g)

**FRONT/REAR WEIGHT DISTRIBUTION HOLE#**

1 2 3 4 5

**WEIGHT(g)**

3

**OPTIONAL WEIGHT**

A2424

A2425

A2705

A2706

**BELT TENSION**

FRONT POS.  REAR POS.

2

2

**UPPERDECK TYPE**

1pc. UPPERDECK TYPE  2pc. UPPERDECK TYPE

Kit

**UPPERDECK SCREW**

A2158

A2158

**REMARKS**

-ETS body height rule!