

Front Suspension:

Ride Height: 23mm
Camber: -1°
Toe: 0°
Arm Type: Flat
Tower Type: Flat
Caster Block Insert: 5°
Bulkhead Type: Plastic
Kick-Up Angle: 25°
Wheel Hex: 5.0mm
Notes:

Anti Roll Bar:
 None
 White (0.8mm)
 Gray (0.9mm)
 Blue (1.0mm)
 Other: _____

Bump Steer Spacing: 2mm

Axle Height:
 +3
 +2
 +1
 0

Ball Stud Spacing: 2mm

Steering Plate: Kit

Steering Stop Spacing: 0

Ball Stud Spacing: 1mm


Caster Block Spacing: 1mm

Rear Suspension:

Ride Height: 23mm
Camber: -1°
Wheel Hex: 7.0mm
Hub Spacing:
 Forward Middle Back
Shock Mounting Position:
 Front of Arm Rear of Arm
Notes:

Anti Roll Bar:
 None
 White (1.2mm)
 Gray (1.3mm)
 Blue (1.4mm)
 Other: _____

Rear Hub Link Setting:



C Mount Inserts: 1° 0.5°

D Mount Inserts: 1° 0.5°

Hub Insert:
 +3 +2 +1 0

Ball Stud Spacing: 3mm

Electronics:


Radio: _____ **Servo:** _____
EPA: Throttle: _____ % Brake: _____ %
ESC: _____
ESC Settings: _____
Motor: _____
Wind: _____ **Timing:** _____
Pinion: _____ **Spur:** _____
Battery: _____
Battery Position: 2R

Drivetrain:

Transmission:
3 Gear: **4 Gear:**
Stand Up: **Lay Down:**
Differential:
Ball Diff: **Gear Diff:**
Notes: Tight
Slipper Clutch:
Type: Kit
of Pads: 2

Shocks:

	Front	Rear
Piston:	2 x 1.6	2 x 1.7
Fluid:	30	30
Spring:	White	Green
Limiters:	2	0
Stroke:	20.0	27.5
Eyelet Length:	Long	Long
Cup Offset:	5mm	5mm
Notes:		



Track Info:

Size: Small Medium Large Extra Large
Surface: Dirt Carpet Astroturf Multi Surface
Traction: Low Medium High Very High
Moisture: Dry Damp Wet
Condition: Indoor Outdoor Dusty Hard Packed
 Bumpy Grooved Smooth Loamy
Temperature: Ambient: _____ Track: _____
Notes:

Tires:

Front Tires: _____
Front Compound: _____
Front Insert: _____
Rear Tires: _____
Rear Compound: _____
Rear Insert: _____
Wheel (F/R): _____
Notes:

Body, Wing, Weight:

Body: Kit
Wing: Kit
Wing Angle: 0° 3° 6°
Servo Weights:
 None Aluminum Steel Other
Electronic Weights:
 None Aluminum Steel Other
Total Vehicle Weight:

Vehicle Comments:

Notes: