

DRIVER, TRACK AND RESULTS

DRIVER	Joris Vervloet	COUNTRY		WEATHER	AIR -1C/30F	TRACK	-1C/30F	Moisture:	Dry
RACE		April 6, 2025	QUALY POS.		STARTING POS.		FINAL POS.		FASTEST LAP
TRACK	RC@CZ	TYPE	Outdoor astroturf	STYLE	☐ TIGHT ☐ MEDIUM ☐ OPEN	Open			
SURFACE GRIP	☐ LOW ☐ MEDIUM ☐ HIGH	High	CONDITION	☐ SMOOTH ☐ ROUGH	Bumpy				
Setup: Zolder				Open in So Dialed App					

FRONT SHOCK ABSORBERS		REAR	
500 cst	OIL	400 cst	
AE Red V2	SPRINGS	Astro 2.1 lb Blue	
3 mm	REBOUND	3 mm	
Int: 1.25 Ext: 0 mm	LIMITERS	Int: 1.25 Ext: 0 mm	
3 x 1.5	PISTONS	3 x 1.6	
Oil brand: Ultimate			
☒ SHORT ☐ LONG	SPRING BUCKETS	☐ SHORT ☒ LONG	
☐ BLADDER	SEAL TYPE	☐ BLADDER	
☒ EMULSION		☒ EMULSION	

ANTI-ROLL BARS	
☐ FRONT	☐ REAR
Front: None	Rear: 1.3mm 2 stripe

REAR DIFFERENTIAL	
☐ BALL DIFFERENTIAL	
☒ GEAR DIFF	10,000 cst
DIFF HEIGHT	3

GEARING	
PINION	Teeth
SPUR GEAR	78 Teeth

ELECTRONICS	
BATTERY	
BRAND	CAPACITY mAh
MOTOR	
BRAND	TYPE
RocketRC	
TIMING	
ESC	
BRAND	TYPE
	Hobbywing

AERODYNAMIC CONFIGURATION	
BODY	Gen3
REAR WING	6.5" 1.5mm
REAR WING WIDTH	REAR WING LIP mm
RR WING ANGLE	☐ 0° ☐ 2° ☒ 4° ☐ 6° ☐ 8° MOUNT ☐ STD ☐ LOW
FRONT WING	☐ YES ☐ NO TYPE

TIRES	
FRONT	Controlled Tire ☐ REAR
MAKE	
TYPE	
COMPOUND	
INSERTS	
Serpent	WHEELS
Serpent	
ADDITIVE	

FRONT		REAR	
CASTER BLOCK INSERTS		SHOCK POSITION	
☒ + ☐ -		☐ REAR ☒ FRONT	
☐ 0 ☐ 2.5 ☒ 5		☐ 0 ☐ 2.5 ☒ 5	
Axle height: Top 1 mm / bottom 2mm		SHIMS 1 mm	
SHOCK POSITION		SHOCK POSITION	
AXLE SPACER		SHIMS 2 mm	
☒ YES ☐ NO		SHIMS 0.5 mm	
SHIMS 1 mm		SHIMS 2.5 mm	
SHIMS 1 mm		WHEEL HEX +1mm	
FRONT CAMBER -1 deg		REAR CAMBER -2 deg	
RIDE HEIGHT 15 mm		RIDE HEIGHT 17 mm	
FRONT BULKHEAD		FRONT CASTER BLOCK	
☐ STOCK ☐ ALU ☒ BRASS		☒ STOCK ☐ ALU	
STEERING SREW ☐ YES ☐ NO		REAR WHEEL BASE	
Arm: Na		REAR ARM	
LONG ☐ SHORT ☒		LONG ☐ SHORT ☒	
FRONT ARM		TRANSMISSION	
SRX2 Hard		Gears: 3	
Layout: Gen3		REAR HUB	
SHORT OFFSET HUB ☒ LONG OFFSET HUB ☐		AXLE HEIGHT	
SHORT ☐ LONG ☒		☐ 0 ☐ 0.5 ☐ 1 ☐ 1.5	
INSERT OFFSET		☐ 2 ☐ 2.5 ☒ 3	
-1 ☐ 0 ☒		REAR FRONT TOE BLOCK	
BUMP STEER		Aluminum narrow	
SPACER ☐ YES ☐ NO		REAR REAR TOE BLOCK	
SHIMS 1 mm		Aluminum narrow	
ACKERMANN		SLIPPER	
☐ OPT.0 ☐ OPT.1 ☒ OPT.2 ☐ OPT.3		☒ STOCK PLATES ☐ VENTED PLATES	
SHIMS 1 mm		Drive type: Slipper	
REAR AXLE		DISTANCE 1.5-2mm from end of shaft	
DRIVETRAIN			
LONG SHAFT ☒ SHORT SHAFT ☐			
Pin: Middle			
LENGTH			
66mm SRX2			
FRONT TOE			
0			
WEIGHT DISTRIBUTION			
CAR WEIGHT grams			
WEIGHT BIAS FR % RR %			
Batt location: Back			
REAR TOE			
0			

REMARKS