

Name:	Date:	Event:	Track:
Track Conditions			
☐ Indoor	☐ Clay	☐ Carpet	☐ Tight
☐ Smooth	☐ Hard Packed	☐ Blue Groove	☐ Wet
Bite: ☐ Low ☐ Med ☐ High			
☐ Outdoor	☐ Dirt	☐ Astro	☐ Open
☐ Rough	☐ Loose/Loamy	☐ Dry	☐ Dusty
Tread: ☐ Pin ☐ Ghost ☐ Slicks	Open in So Dialed App		

Front Suspension

Ride Height	
Camber	
Toe	
Sway Bar	mm

mm Spacer

☐ Composite
☐ Aluminum

☐ 2kpi
☐ 4kpi
☐ 6kpi
☐ 8kpi

mm Spacer

☐ 1.0
☐ 0.5
☐ 0.0

mm Spacer

A B C

☐ 0.7mm
☐ 1.7mm
☐ 2.7mm

mm Spacer

☐ Carbon -2mm
☐ Carbon Std
☐ Carbon +2mm

5
4
3
2
1

mm Spacer

mm Spacer

mm Spacer

Outside
Middle
Inside

☐ 20°
☐ 22.5°
☐ 25°

☐ Composite
☐ Aluminum
☐ Brass + g

Rear Suspension

Ride Height	
Camber	
Sway Bar	mm

mm Spacer

☐ Composite
☐ Aluminum
☐ HRC

B
A
C

☐ 4
☐ 3
☐ 2
☐ 1

mm Spacer

☐ 4.0
☐ 4.5
☐ 5.0
☐ 5.5
☐ 6.0

mm Spacer

mm Spacer

Outside
Inside

☐ Carbon -2mm
☐ Carbon Std
☐ Carbon +2mm

4
3
2
1

☐ X66
☐ X67
☐ X68
☐ X69
☐ Uni

mm Spacer

mm Spacer

☐ 74 ☐ 75

☐ 0 ☐ +1 ☐ +2 ☐ +3 ☐ +4

Chassis

Drive Train	
Diff Type	☐ Ball Diff ☐ Gear Diff
Setting/Fluid	
Internal Gears	☐ Steel ☐ Composite
Planet Gears	☐ 2 ☐ 4
Slipper	☐ Slipper ☐ Direct Drive

Aerodynamics

Body	
Fr Wing	
Rr Wing	
Wicker	
Angle	
Notes	

Tires

	Front	Rear
Brand		
Tread		
Compound		
Insert		
Sauce		
Wheel		
Notes		

Shocks

	Front	Rear
Oil		
Piston Holes		
Piston	☐ 2mm ☐ 2.5mm	☐ 2mm ☐ 2.5mm
Limiter, Int	mm	mm
Shaft Dia	☐ 3.0mm ☐ 3.5mm	☐ 3.0mm ☐ 3.5mm
Limiter, Ext	mm	mm
Stroke	mm	mm
Eyelet	☐ Std ☐ +2mm	☐ Std ☐ +2mm
Spring		
Spring Cup	☐ Low ☐ Mid ☐ High	☐ Low ☐ Mid ☐ High

Electronics

Radio		ESC	
Servo		Thro Prof	
Battery		Timing Adv	
Battery Wt	g	Initial Brake	
Motor		Drag Brake	
Gearing	/	Thr/Bra EPA	/

mm Spacer

☐ 19g
☐ 26g
☐ 37g

☐ +3mm
☐ STD
☐ -3mm

☐ Carbon
☐ Aluminum
☐ Steel

☐ Standard
☐ Stiffezel

☐ Standard
☐ Stiffezel

mm

☐ Soft
☐ Standard
☐ Stiffezel

☐ Standard
☐ Stiffezel

☐ Aluminum
☐ Brass

mm Spacer

☐ 1
☐ 2
☐ 3
☐ 4
☐ 5
☐ Carbon

Total Weight: g Fr/Rr %