SETUP SHEET

SRX2 gen3

SERPENT

DRIVER, TRACK AND RESULTS

DRIVER	RC Zone PR	COUNTRY		WEATHER AIR 29C/85F TRACK 24C/75F	Moisture: Dry
RACE		June 21, 2025	QUALY POS.	STARTING POS. P: 6 FINAL POS.	Best: 15.2 s
TRACK	Rc Zone Carpet	TYPE	Indoor carpet	STYLE ☐ TIGHT ☐ MEDIUM ☐ OPEN ☐	Tight
SURFACE GRIP ☐ LOW ☐ MEDIUM ☐ HIGH ☐	High	CONDITION ☐ SMOOTH ☐ ROUGH ☐	Smooth		
Setup: My Base Setup		Open in So Dialed App			

SHOCK ABSORBERS

FRONT		REAR
40 wt	OIL	35 wt
V1 purple ae	SPRINGS	Astro 2.1 lb Blue
0 mm	REBOUND	0 mm
Int: 1.25 Ext: 0 mm	LIMITERS	Int: 1.25 Ext: 0 mm
2 x 1.6mm	PISTONS	2 x 1.7mm
Oil brand: Team Associated		
☐ SHORT ● LONG SPRING BUCKETS		☐ SHORT ● LONG
☐ BLADDER ● EMULSION	SEAL TYPE	☐ BLADDER ● EMULSION

ANTI-ROLL BARS

☐ FRONT	☐ REAR
Front: 1.2	Rear: 1.1mm 1 stripe

REAR DIFFERENTIAL

● BALL DIFFERENTIAL

☐ GEAR DIFF 30,000 cst

DIFF HEIGHT 0

GEARING

PINION Teeth

SPUR GEAR 78 Teeth

ELECTRONICS

BATTERY
BRAND CAPACITY mAh

MOTOR
BRAND TYPE TIMING

ESC
BRAND TYPE

AERODYNAMIC CONFIGURATION

BODY Lfr

REAR WING 6.5\" 1.5mm

REAR WING WIDTH REAR WING LIP mm

RR WING ANGLE ☐ 0° ☐ 2° ● 4° ☐ 6° ☐ 8° MOUNT ☐ STD ☐ LOW

FRONT WING ☐ YES ☐ NO TYPE

TIRES

FRONT	Controlled Tire ☐	REAR
	MAKE	
	TYPE	
	COMPOUND	
	INSERTS	
Serpent	WHEELS	Serpent
	ADDITIVE	

FRONT

CASTER BLOCK INSERTS ● + ☐ - ☐ 0 ☐ 2.5 ● 5

3 - Mid-out

SHOCK POSITION 1 2 3

Axle height: Top 1 mm / bottom 2mm

SHIMS 0 mm

SHIMS 0 mm

SHOCK POSITION B A

AXLE SPACER ● YES ☐ NO

3 2 1

2 1

FRONT CAMBER -1.5 deg

RIDE HEIGHT 14 mm

FRONT BULKHEAD ☐ STOCK ● ALU ☐ BRASS

FRONT CASTER BLOCK ● STOCK ☐ ALU STEERING SREW ☐ YES ☐ NO

FRONT ARM SRX2

TRANSMISSION Gears: 3 Layout: Gen3

REAR HUB ● SHORT OFFSET HUB ☐ LONG OFFSET HUB

BUMP STEER SPACER ☐ YES ☐ NO SHIMS 0 mm

ACKERMANN ☐ OPT.0 ☐ OPT.1 ☐ OPT.2 ● OPT.3 SHIMS 0 mm

REAR AXLE ● LONG SHAFT SHIMS ☐ SHORT SHAFT

DRIVETRAIN DRIVESHAFT Pin: Middle LENGTH 66mm SRX2

FRONT TOE 0 °

WEIGHT DISTRIBUTION
CAR WEIGHT 1520 grams
WEIGHT BIAS FR % RR %
Batt location: Mid

REAR

SHOCKS POSITION ☐ REAR ● FRONT

A B C

SHIMS 0 mm

SHIMS 0.5 mm

SHOCK POSITION 1 2 3

SHIMS 2.5 mm

WHEEL HEX +1mm

REAR CAMBER -3 deg

RIDE HEIGHT 14 mm

REAR WHEEL BASE Front ● ●

REAR ARM ☐ LONG ● SHORT

REAR UPRIGHT INSERT
AXLE HEIGHT ☐ 0 ☐ 0.5 ☐ 1 ● 1.5 ☐ 2 ☐ 2.5 ☐ 3
INSERT OFFSET -1 ● 0 ☐

REAR FRONT TOE BLOCK Aluminum narrow

REAR REAR TOE BLOCK Aluminum narrow

SLIPPER ● STOCK PLATES ☐ VENTED PLATES
DISTANCE 1.5-2mm from end of shaft
Drive type: Slipper

REAR TOE 0 °

REMARKS