

MTC2R SETUP SHEET

NAME: Will Juskiw	DATE: October 8, 2024
TRACK:	RACE:
TRACK SURFACE:	CARPET ☐ ASPHALT ☐
LAYOUT:	TECHNICAL ☐ MIXED ☐ FAST ☐
TRACTION:	LOW ☐ MEDIUM ☐ HIGH ☐
ELECTRONICS	
SERVO:	ESC:
BATTERY:	MOTOR/TIMING:
NOTES:	
TIRES	
BRAND/TYRE F/R:	
ADDITIVE F/R:	
ADDITIVE TIMING F/R:	

WARMER° F/R:	
TRANSMISSION	
PINION:	SPUR: A2248D(Alu): ☐
DIFF OIL CST: 6,000	OIL WEIGHT (qty.):
BELT TENSION:	FRONT: 1 2 3 4 5 6 7 REAR: 1 2 3 4 5 6 7

FRONT:	SHOCK 'S	REAR:
Bypass	SHOCK CASE:	Standard
4 x 1.3mm	PISTON:	4 x 1.3mm
550 cst g	OIL:	550 cst
6.75T	SPRING:	6.5T
9.5 mm	LENGTH:	9.5 mm
ANTI ROLL BAR		REAR:
FRONT:	1.1 mm	1.2 mm

OPTIONAL WEIGHT				
A2423	A2424	A2425	A2704	A2705
BODYSHELL				
TYPE:	WING TYPE:			
WING POS:	OVERALL WEIGHT:			

STIFFENER: ☐	(mm)
	(mm)
(10mm block)	(mm)
(10mm block)	(mm)
(mm)	(mm)
A2407D (2mm)	(mm)
BODYSHELL	(mm)
(mm)	(mm)
(mm)	(mm)
WINDOW BOTTOM LINE TO BODY POST (mm)	(mm)

FRONT SUSPENSION

☒ A2148
☐ A2148-H
☐ ACTIVE
☒ FIXED

SHIM (mm) 2 CASTER (°) 5 SHIM (mm) 2
 FF (mm) 2 FR (mm) 2
 SHIM (mm) 4
 HEX (mm) 4mm
 CAMBER (°) -2
 SHIM (mm) 1 TOE (°) +1
 RIDE HEIGHT (mm) 5.0
 DOWNSTOP (mm) 5.8
 STEERING ROD POSITION ☒ A2147F ☐ A2467F (-1mm)

NO BODY STOP ☐

STEERING ANGLE in/out: 26 deg

A2158 FRONT BRACE

SHIM UNDER A2435C (mm)

INSIDE ☐ OUTSIDE ☒

A2529 (ALU) ☐

SERVOHORN (mm) 16.5

REAR SUSPENSION

☒ A2148
☐ A2148-H
☐ ACTIVE
☒ FIXED

SHIM (mm) 2 CASTER (°) -3 SHIM (mm) 2
 RR (mm) 2 RF (mm) 2
 SHIM (mm) 2
 HEX (mm) 4mm
 SHIM (mm) 1
 CAMBER (°) -2
 TOE-IN (°) 3
 RIDE HEIGHT (mm) 5.2
 DOWNSTOP (mm) 4.2
 ROD POSITION

INSIDE ☒ OUTSIDE ☐

A2530 (ALU) ☐

CHASSIS/FLEX/WEIGHT DISTRIBUTION

A2414: ☒
 A2415: ☐
 A2434: ☐

F/R DISTRIBUTION

Gr Gr 1 0.005 3

H2412 (18g) ☐

Gr Gr

1 2 3 4 MM SCREW 0.005

A2419

OVERALL WEIGHT (Grs)

UPPERDECK SETTING

A2170: ☐
 A2166: ☐

CUTTING FRONT: MM FLEX SETTING: CUTTING REAR:

OTHER UPPERDECK:

Setup: Crewe

Full details in app: sodialed.com/s/QMiH