

REQUEST FORM FOR CABLES / LINES 

Dear Sommer cable customer,

We offer special requirement conductors by request.

If you could fill in this easy-to-use form and provide us with the required information, it will help us to give you a quote much faster. Best would be, if you could send us a template of the current cables in use, a data sheet or a blueprint.

If none of the above is available, you can also use this form and provide us a little sketch of your requirements.

TYPE (i.e. LIY-CY, video cable / audio cable etc.):

SINGLE CABLE: MULTICORE: HYBRID: FIBRE:

USAGE:

QUANTITY: km ft ft km

One-time order: km recurring order: km est. demand/year km

DESIRED DATE OF DELIVERY:

ORDER SETUP:

Ring: Disposable cardboard reel: Disposable wooden reel:

FIELD OF APPLICATION:

inside outside fix laying occasional movement permanent movement

Temperature range: °C K °F

Sketch specification diagram:

Converter inches mm**COMPOSITION / CONDUCTOR 1:** mm inchessingle-core (solid): multi-core: Litz diameter: mm tin-plated: Copper blank:**For hybrid cables:****COMPOSITION / CONDUCTOR 2:**single-core (solid): multi-core: Litz diameter: mm tin-plated: Copper blank:**COMPOSITION / CONDUCTOR 3:**single-core (solid): multi-core: Litz diameter: mm tin-plated: Copper blank:**COMPOSITION / CONDUCTOR 4:**single-core (solid): multi-core: Litz diameter: mm tin-plated: Copper blank:**COMPOSITION / CONDUCTOR 5:**single-core (solid): multi-core: Litz diameter: mm tin-plated: Copper blank:**CONDUCTOR DIAMETER**(mm²): Conductor 1: Conductor 2: Conductor 3: Conductor 4: Conductor 5: **If hybrid with POWER LEADS:**Max. Volt: Max. Ampere:

Power lead with additional coating insulated:

YES (suitable for free-hanging connections):

NO (i.e. for connections with multi pin connectors):

Fibre cable:

Modes:

Singlemode: 9/125 μm

Multimode: 50/125 μm

Multimode: 62,5/125 μm

Fibre count:



Quality grade: OM2

OM3

OM4

OS2

OS3

Miscellaneous:



Sketch specification diagram:



OVERALL SHIELDING: YES: NO:TYPE OF SHIELDING: Mesh (C-Shield): Spiral (D-Shield): foil (ST):
CU-Blank: SHIELD CU-Tin-plated:**OVERALL OUTER COATING:**Colour (RAL): PVC: PP: PUR:

non-halogen: fire-resistant (FRNC):

Max Diameter: mmText / Print:

Logo: YES NO

(please provide vector data only)

Print with Inkjet (free): Print with Print Wheel (one-off payment for the print wheel 350 EURO):



Customer DetailsCompany: Last name, First name: Custom ID: **SC -**

(if available)

Phone: + eMail:

You can contact our Support by phone from
Monday to Thursday 8.30am to 5pm and
Friday 8.30am to 4.30pm.

Should you have any enquiries about returns, please contact us via:



Phone +49(0)7082/49133-0

eMail: info@sommercable.com