



NL4MP-ST

4 pole chassis connector, black D-size flange, countersunk thru holes, screw termination. This chassis connector is not airtight.

The speakON panel mount connectors are the standard chassis connectors for loudspeaker / amplifier interconnections. They feature a unique metal locking system, making contact only once fully locked. The speakON receptacles are robust, versatile and easy to terminate.

Features & Benefits

- ✓ Current rating 30 A rms
- ✓ Glass reinforced materials make it extremely robust and dependable
- ✓ Precise keyway for secure mating
- ✓ Accurate twist lock latching system
- ✓ Metal insert in locking area

Technical Information

Product	
Title	NL4MP-ST
Connection Type	speakON
Gender	male

Electrical	
Contact resistance	$\leq 3 \text{ m}\Omega$ (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	$> 1 \text{ G}\Omega$ (after dampheat)
Rated current per contact	30 A rms continuous
Rated current per contact	40 A audiosignal, duty cycle 50 %
Rated voltage	250 V ac
Attention	speakON is NOT to be used as an AC mains or power supply connector!
Mechanical	
Lifetime	> 5000 mating cycles
Wiresize	4 mm ²
Wiresize	12 AWG
Wiring	screw terminals
Locking device	Quick Lock
Chassis shape	D
Layout	standard hole position, thru holes
Material	
Contact plating	4 μm Ag
Contacts	Bronze (CuSn6)
Shell	Polyamide (PA 6 30 % GR) black

Environmental

Flammability	UL 94 HB
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C