



Coleman® LX Series Gas Furnaces

- Reliable, efficient blower. Models
 with ECM fan motors improve system
 performance and reduce electricity
 use. Our models with variable-speed
 ECM motors include EcoTrak[™]
 technology that can be fine-tuned to
 your specific climate needs.
- Two-stage burner to save fuel.
 Two-stage gas furnaces can shift their level of performance to track temperatures more accurately and provide greater comfort.
- Reliable aluminized heat exchanger. Advanced, tubular aluminized steel primary heat exchanger allows for high heat transfer and outstanding efficiency.
- Safe, hot-surface ignition and 100% shutoff valve. This technology saves on fuel costs while increasing dependability and reliability.
- Durable, low-leakage cabinet.
 Reinforced cabinets and gasketed doors help ensure warm air goes where it's needed, quietly and efficiently.
- Year-round comfort options.
 For even greater flexibility, a
 Coleman® split system cooling coil can
 be added to handle summer weather.



Rugged reliability is the foundation upon which the iconic Coleman® name is built. And because Coleman® LX Series Gas Furnaces are designed and built in North America by Johnson Controls – a leader in world-class manufacturing – you can rest assured that a Coleman® HVAC heating system will live up to the legacy, providing your family with comfort and energy savings for years to come.

Real-world efficiency

Coleman® LX Series Gas Furnaces can reduce energy costs nearly 40% versus furnaces from just two decades ago. And with up to a 97% Annual Fuel Utilization Efficiency (AFUE) rating on our most efficient models, they have earned some of the highest efficiency ratings in the industry.

Advanced manufacturing
Designed and built in North
America, Coleman® LX Series Gas

Furnaces are crafted using state-of-the-art quality control and assembly processes gleaned from Johnson Controls' advanced manufacturing expertise to provide world-class quality at competitive prices.

Space and budget friendly
A wide range of Coleman® LX
Series Gas Furnaces ensures the right fit
for every home, and every budget.
Compact, 33-inch tall cabinets fit in tight
spaces, allowing for installations in

basements, attics, recreations rooms,

garages, alcoves and even closets. And since all LX Series Gas Furnaces come pre-assembled, wired and tested from the factory, setup is quicker than ever.

Safe for the environment

Coleman® LX Series Gas Furnaces meet U.S. EPA energy efficiency standards, with select models qualifying as ENERGY STAR® products, providing more heat with fewer natural resources. And LoNox (nitrogen oxide) models are also available to meet specific code requirements.

Warmth that endures



We design and build Coleman* products here in North America, where we can closely monitor and improve processes that directly affect quality. It's this commitment to excellence that allows us to offer outstanding warranties, meet the highest industry standards and deliver energy-saving comfort that lasts a lifetime. That's why, when it comes to home comfort, your confidence is our commitment.

LX Series Gas Furnaces

| 27.00.100.000.1.11.10000 | | | | |
|--------------------------|---|------------------------|-------|--|
| MODEL | DESCRIPTION | HEATING INPUT RANGE | AFUE* | LIMITED WARRANTY** |
| ТМ9М | Modulating burner, constant-speed blower | 60–120 Mbh input | 97% | Lifetime heat exchanger, 10-year parts** |
| TM9V | Two-stage operation, variable-speed blower | 40–120 Mbh input | 96% | Lifetime heat exchanger, 10-year parts** |
| ТМ9Т | Two-stage operation with standard efficiency blower | 60–120 Mbh input | 96% | Lifetime heat exchanger, 10-year parts** |
| ТМ9Ү | Two-stage operation with high-efficiency blower | 40–120 Mbh input | 96% | Lifetime heat exchanger, 10-year parts** |
| ТМ9Е | Single-stage operation, high-efficiency blower | 40–120 Mbh input | 95.5% | Lifetime heat exchanger, 10-year parts** |
| TM8V/TMLV+ | Two-stage operation, variable-speed blower | 60–120 Mbh input | 80% | 20-year heat exchanger, 10-year parts** |
| TM8Y | Two-stage operation, high-efficiency blower | 60–120 Mbh input | 80% | Lifetime heat exchanger, 10-year parts** |
| TM8T/TMLT+ | Two-stage operation with standard efficiency blower | 60–120 Mbh input | 80% | 20-year heat exchanger, 10-year parts** |
| TM8X/TMLX† | Single-stage operation, high-efficiency blower | 60–120 Mbh input | 80% | 20-year heat exchanger, 10-year parts** |

* Annual Fuel Utilization Efficiency

† LoNox available.

References to warranty on this literature serve as a guide. For complete details regarding the warranty on your specific equipment, please refer to the warranty certificate in your product manual. For additional product details, such as weight and dimensions, visit www.ColemanAC.com or ask your Coleman® Contractor.



Models TM9V, TM9E and TM9Y are verified to meet ENERGY STAR $^{\circ}$ requirements.

Standard limited warranties:

10 years on parts and heat exchanger coverage of 20 years on 80% AFUE models and lifetime on high-efficiency models.







Complete Assurance™ limited warranty pledge:

If the heat exchanger fails within 5 years of installation, we provide optional furnace replacement in lieu of heat exchanger replacement.







^{**} For 10-year parts and lifetime heat exchanger limited warranties, system must be registered online within 90 days of installation. If not registered within 90 days, the parts warranty reverts to a 5-year limited warranty and the heat exchanger warranty reverts to a 20-year limited warranty.