

## 13 SEER PACKAGE GAS/ELECTRIC, 2 to 5 TONS

Single Phase, 208/230 V, 60 Hz

### REFRIGERATION CIRCUIT

- Environmentally sound R-410A refrigerant
- Scroll compressor standard on all models
- All models with tin-coated copper evaporator coil standard
- Dehumidification mode (airflow reduction) on all models

### EASY TO INSTALL AND SERVICE

- Installs easily on a rooftop or at ground level
- Easy three-panel accessibility for maintenance and installation
- Easily converts to down discharge applications
- Combination gas heating and electric cooling
- Low NOx units available

### BUILT TO LAST

- Hail guard (3/8" spacing) wire grilles standard
- Pre-painted steel cabinet
- Direct spark ignition
- High efficiency ECM indoor blower motor on all models
- Stainless steel tubular heat exchanger
- Vertical condenser fan discharge
- Full perimeter steel base rails
- High and low pressure switches provide added reliability for the compressor

### WARRANTY\*

- 1 year No Hassle Replacement limited warranty
  - Lifetime heat exchanger limited warranty
  - 5 year parts limited warranty (including compressor and coils)
  - With timely registration, an additional 5 year parts limited warranty (including compressor and coils)
- See warranty certificate for complete details.

\* For owner occupied, residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahridirectory.org](http://www.ahridirectory.org).

UNIT PERFORMANCE DATA								
Model Number	Cooling			Heating		Height x Width x Depth in (mm)	Operating Weight lbs (kg)	Notes
	Cap-acity BTU/h	SEER	EER	Input BTU/h	AFUE%			
PGS324040KGP*C	23,000	13.2	11.0	40,000	80.0	40x48-3/16x32-5/8	304 (137)	
PGS324060KGP*C	23,000	13.2	11.0	60,000	80.0	(1016x1224x829)	304 (137)	
PGS330040KGP*C	28,600	13.5	11.2	40,000	80.0	42x48-3/16x32-5/8	309 (140)	
PGS330060KGP*C	28,600	13.5	11.2	60,000	80.0	(1066x1224x829)	309 (140)	
PGS336060KGP*C	34,400	13.0	11.0	60,000	80.0	46x48-3/16x32-5/8	319 (144)	
PGS336090KGP*C	34,400	13.0	11.0	90,000	79.3	(1168x1224x829)	319 (144)	
PGS342060KGP*C	40,500	13.2	11.2	60,000	78.5	40x48-3/16x44-1/8	411 (186)	
PGS342090KGP*C	40,500	13.2	11.2	90,000	80.4	(1016x1224x1123)	411 (186)	
PGS348090KGP*C	46,500	13.2	11.2	90,000	80.4	42x48-3/16x44-1/8 (1066x1224x1123)	419 (190)	
PGS348115KGP*C	46,500	13.2	11.2	115,000	80.3		419 (190)	
PGS348130KGP*C	46,500	13.2	11.2	130,000	78.9		419 (190)	
PGS360090KGP*C	57,000	13.4	11.0	90,000	80.4		419 (190)	
PGS360115KGP*C	57,000	13.4	11.0	115,000	80.3		441 (200)	
PGS360130KGP*C	57,000	13.4	11.0	130,000	78.9		441 (200)	

\* - 0 = Standard, 1 = Low NOx