



- > 34" cabinet height on all models
- 2 5 ton models available in each family
- Multiple venting options offered in each poise
- Durable, galvanized steel cabinets
- Select models are compliant with California 40ng/J Low-NOx requirements (see below)

Model Numb	er CA Low NOx Model Number	Input BTU/h	Nominal Airflow (Tons)	Dimensions (Inches) H x W x D	Motor Type	Application	AFUE	
------------	-------------------------------	----------------	------------------------------	-------------------------------------	------------	-------------	------	--

A801X CONSTANT TORQUE 80% AFUE

A801X026AM2SCA	A801X026AM2TCA	26,000	2	34 x 14.5 x 28.75	Constant Torque (ECM)	Multi-position	80%
A801X040BM2SCA	A801X040BM2TCA	40,000	2-3	34 x 14.5 x 28.75	Constant Torque (ECM)	Multi-position	80%
A801X040AM3SCA	A801X040AM3TCA	40,000	2	34 x 17.5 x 28.75	Constant Torque (ECM)	Multi-position	80%
A801X060BM4SCA	A801X060BM4TCA	60,000	4	34 x 17.5 x 28.75	Constant Torque (ECM)	Multi-position	80%
A801X080BM4SCA	A801X080BM4TCA	80,000	3-4	34 x 17.5 x 28.75	Constant Torque (ECM)	Multi-position	80%
A801X080CM5SCA	A801X080CM5TCA	80,000	4-5	34 x 21 x 28.75	Constant Torque (ECM)	Multi-position	80%
A801X100CM5SCA	A801X100CM5TCA	100,000	4-5	34 x 21 x 28.75	Constant Torque (ECM)	Multi-position	80%
A801X120DM5SCA	A801X120DM5TCA	120,000	5	34 x 24.5 x 28.75	Constant Torque (ECM)	Multi-position	80%

5 YEAR WARRANTY

Limited functional parts warranty

10 YEAR WARRANTY

Functional parts warranty with product registration