

Residential Electric Water Heaters

Easy to install, service and maintain, our residential electric models are just one more reason why Bradford White is the best choice for all your water heater needs.



- Hydrojet® Total Performance System Reduces Sediment Buildup
- Vitraglas™ Lining Provides Superior Tank Protection
- Silent Heat Traps Increase Energy Savings and Reduce Noise Potential
- Immersed Copper Heating Elements with kW Input Range from 1.5kW to 12kW
- Factory-Installed Dielectric Waterway Fittings
- User-Friendly Junction Box Allows Easy Access for Electrical Connections
- Low Restriction Brass Drain Valve
- Standard Six-Year Limited Tank & Parts Warranty with Ten-Year Option Available

Committed to the Professional.


BRADFORD WHITE[®]
WATER HEATERS
www.bradfordwhite.com

Count on Bradford White Residential Electric water heaters for easy installation, high efficiency, and outstanding performance.



Upright Models

Model Number	Nominal Capacity (Gal.)	DOE Rated Storage Volume (Gal.)	First Hour Rating (Gal.)	Uniform Energy Factor	Height In.	Dia. In.	Approx. Shipping Weight lbs.
RE330S6	30	27	47	0.92	47	20	100
RE340S6	40	36	54	0.93	47 ^{7/8}	22	114
RE340T6	40	36	55	0.93	60 ^{5/8}	20	125
RE350S6	50	45	63	0.93	47	24	144
RE350T6	50	45	64	0.93	58 ^{5/8}	22	138
RE240S6†	40	36	54	0.93	48	20	123
RE250S6†	50	45	63	0.93	47	22	143

- † Models include supplied insulation blanket (2" thick). Dimensions in charts above do not include blanket thickness.
- All Upright models feature two heating elements that can be wired for either simultaneous or non-simultaneous operation.



Lowboy Models

Model Number	Nominal Capacity (Gal.)	DOE Rated Storage Volume (Gal.)	First Hour Rating (Gal.)	Uniform Energy Factor	Height In.	Dia. In.	Approx. Shipping Weight lbs.
RE120L6††	19	—	—	—	24 ^{7/8}	18	65
RE130L6**	28	26	42	0.92	29 ^{3/4}	20	99
RE230LN6	28	26	47	0.92	30	23	102
RE230L6**	28	26	46	0.92	29 ^{7/8}	22	108
RE240LN6	37	34	50	0.92	32	24 ^{1/2}	126
RE240L6**	38	35	54	0.93	32 ^{5/8}	24	140
RE250L6**	47	43	63	0.93	33 ^{5/8}	26	173

- ** Models include supplied insulation blanket (2" thick). Dimensions in charts above do not include blanket thickness.
- †† Exempt from ASHRAE 90.1b (current standard). Uniform Energy Factor and First Hour Rating is based on the latest AHRI directory listings.
- The Lowboy is perfect for tight installations such as a closet or under a counter.

All models below are exempt from NAECA requirements and ASHRAE Standard 90.1b. for each of these products categories



Utility Models

Model Number	Gallon Capacity	GPH Recovery 90° F Rise	Height In.	Diameter In.	Approx. Shipping Weight lbs.
RE16U6	6	7	16 ^{1/2}	14	35
RE110U6	10	7	17 ^{1/2}	16	44
RE112U6	12	7	16 ^{7/8}	18	53
RE112T6	12	7	27 ^{3/4}	14	48
RE115U6	15	7	20 ^{1/4}	18	58
RE120U6	19	7	24 ^{3/4}	18	65


- Utility models have side water connections allowing installations in tight spaces.
- Six and twelve gallon Utility models offer alternative top connections for additional piping flexibility.



Wall Hung Models

Model Number	Gallon Capacity	GPH Recovery 90° F Rise	Height In.	Diameter In.	Approx. Shipping Weight lbs.
RE16WV6	6	7	15 ^{3/4}	14	37
RE112WV6	12	7	16 ^{3/8}	18	54
RE120WV6	19	7	24 ^{3/8}	18	67

- These space-saving water heaters can be mounted on walls, freeing up valuable floor space.
- Water connections are conveniently located on the bottom of the water heater for ease of installation.



Powerful Compact® Model

Model Number	Gallon Capacity	GPH Recovery 90° F Rise	Height In.	Diameter In.	Approx. Shipping Weight lbs.
RE1-2U6	2	7	12 ^{1/4}	9 ^{7/8}	13

- Can be installed almost anywhere - under a sink, inside cabinets or hung on a wall (must order mounting bracket).
- Includes a 4ft. power cord with 3 prong grounded plug (20 amp circuit required).



Built to be the Best™ | 800.523.2931

©2017, Bradford White Corporation. All rights reserved.

RELC-SS 1017

BRADFORD WHITE
WATER HEATERS
www.bradfordwhite.com