

619PHA High Wall

Sizes: 09 / 12

ENERGY STAR® certified, based on outdoor unit pairing

Indoor Features:

- Available in 208/230V
- Relative Humidity Sensor
- Occupancy sensor
- Up to 42.0 SEER and 15.0 HSPF when paired with 38MPRA outdoor unit
- Modes: Cool, Heat, Dry, Fan, Auto
- Turbo Mode
- Fully modulating fan speeds
- Sleep Mode
- Up-down / right-left louver control (fixed or swing)
- ECO Mode
- Carbon filter
- Follow Me (senses temperature at handheld remote)
- Heating Setback (46° F Heating Mode)
- Quiet indoor operation, as low as 29 dB(A)
- Aluminum Golden Hydrophilic pre-coated fins

Controls:

- Built-in Wi-Fi® to control unit anywhere, anytime
- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA (7-Day programmable)

Accessories:

- Condensate Pump (230V optional)
- Insulated 25' Lineset
- 24V Interface for compatibility with conventional thermostat

Compatible with:

- 38MPRA Outdoor Unit Single Zone
- 38MGR Outdoor Unit Multi-Zone



Today's lifestyles demand more than yesterday's technology. Your home's heating and air conditioning needs can be met with new, more efficient and advanced systems. The Bryant Evolution® 619PHA High Wall, when paired with the 38MPRA single zone, has our highest efficiency rating at 42 SEER. There's nothing more efficient¹! The High Wall is also compatible with the 38MGR multi-zone to be flexible to fit any application. Along with the technology to optimize the comfort of any home, such as built-in Wi-Fi® to control your system anywhere or being compatible with third party thermostats, thanks to the 24V Interface. In addition, the unit has a smart sensor technology that not only detects the temperature in the room but also the humidity level. With the use of the Wireless Controller, you can customize the humidity level to your preference. This system has an occupancy sensor that senses a person in a room and can direct airflow either toward or away from that person. Doesn't your home deserve the best?



Condensate Pump
53DS-900---118 (208/230V)



Optional Wired Controller
(7-Day Programmable)
KSACN0401AAA

EVOLUTION
SYSTEM

¹ According to system ratings maintained by AHRI as of January 22, 2018, in accordance with the AHRI Unitary Small Equipment Operations Manual. The 9,000 Btu/h single zone ductless has a 42 SEER Rating.

619PHA High Wall

HEAT PUMP				
Size			9	12
System	Indoor Model		619PHAQ09XA3	619PHAQ12XA3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60	208/230-1-60
	Power Supply		Indoor unit powered from outdoor unit	
	MCA	A.	0.3	0.3
Controls	Wireless Remote Controller (° F/° C Convertible)		Standard	Standard
	Wired Remote Controller (° F/° C Convertible)		Optional	Optional
Operating Range	Cooling Indoor DB Min -Max	° F (° C)	62~90 (17~32)	62~90 (17~32)
	Heating Indoor DB Min -Max	° F (° C)	57~68 (14~20)	57~68 (14~20)
Piping	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	3/8 (9.52)	1/2 (12.7)
Indoor	Unit Width	in (mm)	35.2 (895)	35.2 (895)
	Unit Height	in (mm)	11.7 (298)	11.7 (298)
	Unit Depth	in (mm)	9.8 (248)	9.8 (248)
	Net Weight	lbs (kg)	37.48 (17)	37.48 (17)
	Number of Fan Speeds		4	4
	Airflow (lowest to highest)	CFM	144/245/295/345	168/252/306/357
	Sound Pressure (lowest to highest)	dB(A)	29/35.5/41.5/45.6	29/35.5/41.5/46.8
	Air Throw Data	ft (m)	21.98 (6.7)	22.97 (7)
	Moisture Removal	Pint/h (L/h)	2.11 (1.0)	2.53 (1.2)
	Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	1 (25.4)

Compatibility Table			
Indoor Unit		619PHAQ09XA3	619PHAQ12XA3
Outdoor Unit Single Zone*		38MPRAQ09AA3	38MPRAQ12AA3
		38MGRQ18B--3	
Outdoor Unit Multi-Zone*		38MGRQ24C--3	
		38MGRQ30D--3	
		38MGRQ36D--3	
		38MGRQ48E--3	

* Performance may vary based on the compatible outdoor units. See respective pages for performance data.



Visit our website at BryantDuctless.com

7310 West Morris Street, Indianapolis, IN 46231

Manufacturer reserves the right to discontinue, or change at any time, specification or designs without notice or without incurring obligations.