



# Compass Series



## Water-to-Water Unit Single-Stage



Other state or provincial credits may apply.



GeoComfort's single-stage water-to-water models are small in size and big on efficiency. These hydronic systems are designed to supply heated or chilled water for use in a wide range of heating and cooling applications, the most remarkable of which is radiant floor heating. This extremely comfortable heating solution warms your home from the floor up, allowing for constant and uniform heat distribution that eliminates hot and cold spots. The system is also reversible and capable of providing chilled water for air conditioning.



[www.geocomfort.com](http://www.geocomfort.com)

*Maximum comfort and maximum efficiency.  
You can have both!*

# Live comfortably.®

## Satisfaction:

- GeoComfort single-stage water-to-water models utilize stainless steel brazed plate heat exchangers, a time-tested technology that makes them incredibly efficient.
- The service-friendly design simplifies installation and allows the contractor easier access to your system in order to keep it operating at peak efficiency.

## Comfort:

- Warm floors for comfortable, even heat.
- Zoning options allow you to independently control the temperature in each part of your house.

## Flexibility:

- GeoComfort hydronic systems can be used in various applications other than space conditioning including domestic hot water, pool and spa heating, and snow/ice melt.

## Incentives



The system meets ENERGY STAR® requirements for efficiency, qualifying it for the United States 30% federal tax credit and other state incentives, or in Canada, provincial incentives.

## Efficiency:

For every one unit of energy the heat pump uses in operation, the system collects three to four free units from the earth, which means you get four to five units of heat for the cost of one!



**For a different kind of comfort**, ask your installer about the GeoComfort standard warranty, the Peace of Mind Warranty option, and other warranty choices.

## Unit Performance (Ground Loop Heat Pump)

Model	Capacity	Cooling		Heating	
		BTU/H	EER	BTU/H	COP
Single Compressor Water-to-Water Models					
GWS036	Full Load	36,100	17.3	31,600	3.1
GWS048	Full Load	49,400	16.6	45,700	3.2
GWS060	Full Load	58,100	16.6	53,700	3.2
GWS072	Full Load	72,500	16.7	62,800	3.1
GWS084	Full Load	84,300	16.1	70,100	3.1

### Notes:

Rated in accordance with ISO Standard 13256-2 which includes Pump Penalties.


Heating capacities based on 32°F EST & 104°F ELT.

Cooling capacities based on 77°F EST & 53.6°F ELT.

Entering load temperature over 120°F heating and under 45°F Cooling is not permissible.

Floor heating is most generally designed for 85°F entering load temperature.

Enertech Global is continually working to improve its products. As a result, the design, specifications, and general information of each product may change without notice and may not be as described herein. For the most up-to-date information, please visit our website, or contact our Customer Relations department at [customerrelations@enertechusa.com](mailto:customerrelations@enertechusa.com). Statements and other information contained herein are not express warranties and do not form the basis of any bargain between the parties, but are merely Enertech Global's opinion or commendation of its products.



Common water-to-water geothermal installation



GeoComfort geothermal systems are manufactured by Enertech Global and proudly built in the Heart of America – Mitchell, South Dakota. Enertech Global systems are built with stringent quality control standards and the most comprehensive testing within the geothermal heating and cooling industry.

