# ENDEAVOR



# Endeavor™ Line Classic Plus® Series iM Heat Pumps



# Heat Pump

Cooling Efficiency: 15.2 SEER2/ 11.7 EER2

**Heating Efficiency:** 7.8 HSPF2

**Nominal Sizes:** 

2 to 4 Tons (6.68 kW to 13.36 kW)

Cooling Capacities: 13.36 kBTU to 45.6 kBTU



#### **Features:**

#### • Two-Stage Scroll Compressor:

Features two speeds (high and low) of cooling and heating, providing more precise temperature control, lower humidity and greater efficiency when compared to single stage compressors

# • 7mm Condenser Copper Coil1:

Requires less refrigerant allowing for a smaller and lighter footprint while enhancing reliability

### • Inverted Reversing Valve:

Allows for faster heat transfer with gravity assist shifting and reduced joint stress for increased reliability

# • PlusOne Expanded Value Space:

3" – 4" – 5" service valve space – provides a minimum working area of 27-square inches for easier access

# • PlusOne Triple Service Access:

15" wide, industry leading corner service access, two fastener, removeable corner and individual louver panels – makes repairs easier and faster

<sup>&</sup>lt;sup>1</sup> Does not apply to the 5 ton model

#### Rheem<sup>®</sup> Endeavor<sup>™</sup> Line Classic Plus<sup>®</sup> Series iM Heat Pumps - RP15AZ Nomenclature

<u>R</u>	<u>P</u>	<u>15</u>	<u>A</u>	<u>Z</u>	<u>24</u>	<u>A</u>	Ī	<u>2</u>	<u>N</u>	<u>A</u>
Brand	<b>Product Category</b>	SEER2	Region	Refrigerant	Capacity BTU/HR	Major Series	Voltage	Туре	Controls	Minor Series
Rheem	P - Heat Pumps	15.2 SEER2	A-All		24 - 24,000 [7.03 kW]		J - 1ph, 208-230/60	2 - 2+ Stage	N - Non-Comm	A - 1st Design
					36 - 36,000 [10.55 kW]					
					48 - 48,000 [14.07 kW]					

Available Models
RP15AZ24AJ2NA
RP15AZ36AJ2NA
RP15AZ48AJ2NA



#### **Cabinet Dimensions**

Model	Height (in)	Width (in)	Depth (in)	Net Weight (lbs)
RP15AZ24AJ2NA	25	29.75	29.75	150
RP15AZ36AJ2NA	39	33.75	33.75	214
RP15AZ48AJ2NA	39	33.75	33.75	240

#### **Preliminary Product Data<sup>2</sup>**

Model	Total Capacity BTU/H [kW]	SEER2	EER2	HSPF2	Voltage	Phase	Hertz
RP15AZ24AJ2NA	22,800 [6.7]	15.2	11.7	7.8	208-230	1	60
RP15AZ36AJ2NA	34,200 [10.0]	15.2	11.7	7.8	208-230	1	60
RP15AZ48AJ2NA	46,000 [13.5]	15.2	11.7	7.8	208-230	1	60

<sup>&</sup>lt;sup>2</sup> COMING SOON: Ratings data is for reference only. Complete rated system performance data will be included in the full Product Specification Sheet. Please refer to www.ahridirectory.org for official ratings.

#### **GENERAL TERMS OF LIMITED WARRANTY**<sup>3</sup>

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Conditional Parts (Registration Required).....Ten (10) Years

<sup>3</sup> For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the

Manufacturer for a copy of the product warranty certificate.

Rheem Heating, Cooling & Water Heating • 5600 Old Greenwood Road Fort Smith, Arkansas 72908 • www.rheem.com

Rheem Canada Ltd./Ltée • 125 Edgeware Road, Unit 1 Brampton, Ontario • L6Y 0P5