APPENDIX A. Finish Codes

SECTION A. ALUMINUM ALLOYS

CODE	APPLICABLE FINISH
A969	**WHITE URETHANE, P5438-2 COATING, AND 16NXXXX FINISH - ALUMINUM ALLOYS PREVIOUSLY PRIMED.**
	A APPLY FMS-3049 COATING TO SPECIFIED SURFACES PER 532.
	B PAINT SPECIFIED SURFACES WITH WHITE URETHANE COATING PER 222 (OR 274).
	C PAINT SPECIFIED SURFACES WITH LIGHT GRAY URETHANE COATING PER 254 (OR 276).
	D APPLY P5438-2 RAIN EROSION RESISTANT COATING TO SPECIFIED SURFACES PER 515.
	E FINISH EXTERIOR EXPOSED SURFACES AFTER ASSEMBLY PER THE APPLICABLE 16NXXXX AIRCRAFT PAINTING DRAWING.
	F TOUCH UP AS REQUIRED PER 237 AND FPS-3057.
A970	**REWORK OF CURED PRIMER - WHITE URETHANE. ALL ALUMINUM ALLOYS COVERED WITH CURED PRIMER.**
	A CLEAN AND ACTIVATE CURED PRIMER PER 174.
	B PAINT SPECIFIED SURFACES WITH WHITE URETHANE PER 222.
	C TOUCH UP AS REQUIRED PER 237.
A971	**PRIMER, WHITE URETHANE AND 16NXXXX FINISH BARE 2000 AND 7000 SERIES ALLOYS**
	A ANODIZE ALL SURFACES PER 111.
	B PRIME ONE COAT ALL SURFACES PER 531.
	C PAINT INTERIOR SURFACES AFTER ASSEMBLY WITH WHITE URETHANE PER ASSEMBLY FINISH CODE.
	D FINISH EXTERIOR EXPOSED SURFACE AFTER ASSEMBLY PER THE APPLICABLE 16NXXXX AIRCRAFT PAINTING DRAWING.
	E TOUCH UP AS REQUIRED PER 235 AND 536.
	F NOTE: FOR APPLICATION OF FMS-3049 COATING; SEE MATERIALS AND PROCESSES ENGINEERING FOR USE.