

Multi Cover 610

Application

- General-purpose coverage and protection applications
- Tarpaulins
- Sporting covers
- Gym landing mats and punching bags
- Tents, camping & caravan equipment
- Banners
- Blind edging



Flame
Retardant



REACH, RoHS,
VCA compliant

5 YEAR*
LIMITED
WARRANTY

Multi Cover 610

Semi Coated PVC Polyester Fabric

Standard Roll Size:

2050mm x 30m / roll
*Custom widths and lengths
 available upon request.*

Standard Colors:

- White • Red • Dark Green • Grey
- Beige • Pink • Light Blue • Black
- Yellow • Purple • Mid Blue
- Orange • Light Green • Royal Blue

Properties	Test Method	Result	Unit
Yarn	High-tensile, woven polyester - standard weave		
Total Weight	DIN EN ISO 2286-2	610 18	g/sq.m oz/sq.y
Yarn (W/F)	DIN EN ISO 2060	1000/1300 1100/1430	Denier Dtex
Threads (W/F)	DIN EN ISO 1049-2	18/17 7/7	Per inch Per cm
Tensile Strength (W/F)	DIN 53354	291/285 2851.8/2793 325/318	Kg/5cm N /5cm lbs/inch
Tear Resistance (W/F)	DIN 53363	36/38 352.8/372 79/84	Kg/5cm N/5cm Lbs/inch
Welding Adhesion	DIN 53357	10.2 100 11.4	Kg/5cm N /5cm Lbs/inch
Temperature Resistance	DIN 53361	-30 ~ +70	°C
Max Width	DIN EN ISO 2286-1	3.2 126	Meter Inch
Flex Cracking Resistance	AS 1441.6 - 1973	400,000	Cycles
Additives	UV, Anti Crack to -30°, Anti-Static, FR treatment to AS 2755.2, Matt Finish		
Environmental	Meets ROHS, REACH & VCA requirements		