



**ROFAB**  
industrial fabrics

# Multi Cover LITE 500

## Application

- Light weight static covers & tarpaulins
- Sports equipment
- Landing mats
- Fumigation covers
- Caravan & camper draft skirts
- Promotional umbrellas
- Swag bases
- Tent floors
- Tool bags
- Barriers
- Aprons
- Bunting
- Banners



Flame  
Retardant



REACH, RoHS,  
VCA compliant

**2 YEAR\***  
LIMITED  
WARRANTY

## Multi Cover LITE 500

Semi Coated PVC Polyester Fabric

### Standard Roll Size:

2050mm x 40mt / roll  
*Custom widths and lengths  
 available upon request.*

### Standard Colors:

- White
- Slate Grey
- Sandbank
- Beige
- Yellow
- Orange
- Red
- Outback Red
- Royal Blue
- Storm Blue
- Storm Grey
- Charcoal
- Black

| Properties                    | Test Method                                    | Result                          | Unit                         |
|-------------------------------|------------------------------------------------|---------------------------------|------------------------------|
| <b>Yarn</b>                   | Semi coated PVC polyester fabric               |                                 |                              |
| <b>Total Weight</b>           | DIN EN ISO 2286-2                              | 500<br>14.7                     | g/sq.m<br>oz/sq.y            |
| <b>Yarn (W/F)</b>             | DIN EN ISO 2060                                | 1000/1000<br>1100/1100          | Denier<br>Dtex               |
| <b>Threads (W/F)</b>          | DIN EN ISO 1049-2                              | 18/13<br>7/5                    | Per inch<br>Per cm           |
| <b>Tensile Strength (W/F)</b> | DIN 53354                                      | 210/125<br>2058/1225<br>235/140 | Kg/5cm<br>N /5cm<br>lbs/inch |
| <b>Tear Resistance (W/F)</b>  | DIN 53363                                      | 25.5/15<br>249.9/147<br>56/33   | Kg/5cm<br>N/5cm<br>Lbs/inch  |
| <b>Welding Adhesion</b>       | DIN 53357                                      | 9<br>88.2<br>10.1               | Kg/5cm<br>N /5cm<br>Lbs/inch |
| <b>Temperature Resistance</b> | DIN 53361                                      | -30 ~ +70                       | °C                           |
| <b>Max Width</b>              | DIN EN ISO 2286-1                              | 3.5<br>137.8                    | Meter<br>Inch                |
| <b>Additives</b>              | NFPA-701,DIN4102-B1,NFP92-507 M2, Satin Finish |                                 |                              |
| <b>Environmental</b>          | EN-71, 6P, ROHS, REACH                         |                                 |                              |