



ROFAB
industrial fabrics

Unicoat 900

Application

- Machinery and agricultural product covers
- Roll over truck tarps and curtains
- Builders tarps
- Spill containment
- Fumigation covers



Flame
Retardant



REACH, RoHS,
VCA compliant

7 YEAR*
LIMITED
WARRANTY

Unicoat 900

Full Coated PVC Polyester Fabric

Standard Roll Size: 3200mm x 30m / roll <i>Custom widths and lengths available upon request.</i>	Standard Colors: White Red Dark Blue Yellow Dark Green Dark Grey Orange Royal Blue Black		
---	---	--	--

Properties	Test Method	Result	Unit
Yarn	High-tensile, woven polyester – panama weave		
Total Weight	DIN EN ISO 2286-2	900 26.5	g/sq.m oz/sq.y
Yarn (W/F)	DIN EN ISO 2060	1000/1000 1100/1100	Denier Dtex
Threads (W/F)	DIN EN ISO 1049-2	30/30 12/12	Per inch Per cm
Tensile Strength (W/F)	DIN 53354	430/390 4214/3822 480/436	Kg/5cm N /5cm lbs/inch
Tear Resistance (W/F)	DIN 53363	66/55 646.8/539 146/121	Kg/5cm N/5cm Lbs/inch
Welding Adhesion	DIN 53357	13 127.4 14.5	Kg/5cm N /5cm Lbs/inch
Temperature Resistance	DIN 53361	-30 ~ +70	°C
Max Width	DIN EN ISO 2286-1	3.5 137.8	Meter Inch
Additives	UV, Anti Crack to -30°, Anti-Static, FR treatment to AS 2755.2, Gloss lacquer to two sides		
Environmental	Meets ROHS, REACH & VCA requirements		