
MULTI COVER 610™

Typical Specifications

PVC COATED POLYESTER FABRIC

As its name suggests, **Multi Cover 610** is a versatile fabric which is ideal for general-purpose coverage and protection. **Multi Cover** can be used in a wide variety of applications, from tarpaulins and sporting covers, to gym landing mats and punching bags, tents, camping & caravan equipment, banners and blind edging. It has a flat matte surface and a soft formulation to allow easy handling & processing during fabrication whilst offering a non-reflective and non-slip finish to the final product.



Properties	Test Method	Result	Unit	
Total Weight	DIN EN ISO 2289-2	610	gsm / sq.m	
Yarn (Warp / Weft)	DIN EN ISO 2060	1000 / 1300	Denier	
		1100 / 1430	Dtex	
Threads (Warp / Weft)	DIN EN ISO 1049-2	18 / 17	Per inch	
		7/7	Per cm	
Tensile Strength (Warp / Weft)	DIN 53354	291 / 285	Kg / 5cm	
		2852 / 2793	N / 5cm	
		325 / 318	Ibs / inch	
Tear Resistance (Warp / Weft)	DIN 53363	36 / 38	Kg	
		353 / 372	N	
		79 / 84	Lbs	
Welding Adhesion	DIN 53357	10.2	Kg / 5cm	
		100.0	N / 5cm	
		11.4	Lbs / inch	
Temperature Resistance	DIN 53361	-30 to +70	°C	
Environmental	Meets ROHS, REACH & VCA requirements			
Additives	UV, Anti Crack to -30°, Anti-Static, FR Treatment			
FR Treatment	AS1530 part 2 & AS1530 part 3 t	AS1530 part 2 & AS1530 part 3 test results available on request		
Surface	Matte			
Warranty	5 years conditions apply			
Stock Roll Size	2050mm x 30m / roll	2050mm x 30m / roll		



