
SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 7051 Numbering Machine Ink

COLORS: All colors

MANUFACTURER: Specialty Ink Company, Inc.
ADDRESS: 20 Dunton Avenue
Deer Park, NY 11729

EMERGENCY PHONE: 800-688-4005 - VEOLIA
OTHER CALLS: 631-586-3666
FAX PHONE: 631-586-3666

PREPARED BY: Keith Werwa

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS NO.</u>	<u>% VOL</u>	<u>SARA 313 Reportable</u>	<u>Exposure Limit ACGIH-TLV</u>	<u>Exposure Limit OSHA PEL</u>
Petroleum Distillates	64745-52-5	85-100	No	10MG/M3	5 MG/M3

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Do not get in eyes, on skin or clothing. Do not breathe vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

ROUTES OF ENTRY: Dermal contact. Eye contact. Inhalation. Ingestion.

POTENTIAL HEALTH EFFECTS

EYES: Non irritating.

SKIN: No significant adverse health effects.

INGESTION: Harmful effects not anticipated from swallowing small amounts.

INHALATION: No adverse effects are anticipated from single exposure to vapor.

CHRONIC HEALTH HAZARDS: Mild skin irritant

SECTION 4: FIRST AID MEASURES

EYES: Flush eyes with water.

SKIN: Wash with soap and water.

INGESTION: **Don not** induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention and advice immediately.

INHALATION: No significant adverse health effects.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: NA
(% BY VOLUME) LOWER: NA

FLASH POINT: 305 F
METHOD USED: Closed cup

AUTOIGNITION TEMPERATURE: 600 F

NFPA HAZARD CLASSIFICATION

HEALTH: 0
OTHER: 0

FLAMMABILITY: 0

REACTIVITY: 0

HMIS HAZARD CLASSIFICATION

HEALTH: 0
PROTECTION: B

FLAMMABILITY: 0

REACTIVITY: 0

EXTINGUISHING MEDIA: Carbon dioxide. Dry chemical. Water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode. Use waterspray to cool fire exposed area. Use watersparay to protect personnel.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Keep unnecessary personnel away. Use suitable protective equipment (Section 8).

ENVIRONMENTAL PRECAUTIONS: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

METHODS FOR CLEANING UP:

Small spill and leak: Absorb with an inert material and place in an appropriate waste disposal container.

Large spill and leak: Use appropriate containment to avoid environmental contamination. Place spilled material in an appropriate container for disposal.

SECTION 7: HANDLING AND STORAGE

HANDLING: Keep container closed. Use with adequate ventilation.

STORAGE: Keep container tightly closed. Keep container in a cool, well ventilated area. Avoid strong oxidants and acids.

STORAGE TEMPERATURE: 60-80 F

SHELF LIFE:

12 months from date of manufacture

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide exhaust ventilation. Ensure that eyewash stations and safety showers are proximal to the work-station location

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

EYE PROTECTION: Safety eyewear complying with an approved standard should be use when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

SKIN PROTECTION: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

PERSONAL PROTECTION IN CASE OF LARGE SPILL: Splash goggles. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE AND APPEARANCE: Oily Liquid

ODOR: Mild Oil

BOILING POINT: 450 F

MELTING POINT: -25 F

VAPOR PRESSURE (mmHg): 0.1 mm hg

VAPOR DENSITY (AIR = 1): > 10

SPECIFIC GRAVITY (H₂O = 1): .90

REACTIVITY IN WATER: None

SOLUBILITY IN WATER: Insoluble

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Extremely high temperatures , open flame

INCOMPATIBILITY (MATERIAL TO AVOID): Oils will swell rubber

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: excessive heating may produce CO₂

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID (POLYMERIZATION): None

SECTION 11: TOXICOLOGICAL INFORMATION

N/A

SECTION 12: ECOLOGICAL INFORMATION

N/A

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. The user of this material has the responsibility to dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (LAND, D.O.T.)
NOT REGULATED

WATER TRANSPORTATION (WATER, I.M.O.)
NOT REGULATED

AIR TRANSPORTATION (AIR, I.C.A.O.)
NOT REGULATED

SECTION 15: REGULATORY INFORMATION

N/A

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: The hazards listed on this MSDS are taken from the MSDS for each of the ingredients in this mixture. In most cases, the maximum form of hazard is represented here. The TLV's represent the conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect . It must be remembered that each individual reacts differently and some may experience discomfort while others do not. This MSDS is presented so that each individual will have the information to deal safely with the use of this product. All material's TSCA listed.

PREPARATION INFORMATION: Prepared by Specialty Ink Company, Inc.

DATE PREPARED: November 3, 2011
SUPERSEDES ALL PREVIOUSLY DATED MSDS

DISCLAIMER: As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim all liability for any use of this material. Information contained herein is given in good faith and is believed to be true and accurate. All statements or suggestions are made without any warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or results to be obtained from the use thereof.