



DECLARATION OF PERFORMANCE
In accordance with annex III of Regulation (EU) 305/2011
(Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No 574/2014

No. 24412-CPR/2013

1. Unique identification code of the product-type:

ARDEX EG 8 PLUS

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

See batch number and date of manufacture on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Reaction Resin Adhesive

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

**ARDEX UK Ltd,
Homefield Road,
Haverhill,
Suffolk,
CB9 8QP**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 12004:2007+A1:2012

The notified body **LGAI TECHNOLOGICAL CENTRE, S. A./APPLUS** with the identification number **0370** performed the test according to EN 12004:2007 under **System 3** and issued the following:

Test Report No. 15/11410-2467

Reaction to fire performance has been declared in accordance with the Commission Decision of 9th February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 12004:2007 +A1:2012
Bond strength as: - initial shear adhesion strength	$\geq 2.0\text{N/mm}^2$	
Durability for: - shear adhesion strength after water immersion - shear adhesion strength after thermal shock	$\geq 2.0\text{N/mm}^2$ $\geq 2.0\text{N/mm}^2$	
Open Time:	$\geq 0.5\text{N/mm}^2$ after not less than 20 min	
Slip:	NPD	
Release of dangerous substances	See SDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ian Smith
Laboratory Manager

Haverhill 11/02/2016