

Fit for purpose.

Whatever the final finish, iTe has the correct adhesive for your flooring project.

The **iTe Products®** range of flooring adhesives ensures the perfect finish, and avoids health and safety issues with lifting carpet tiles and flooring. Free of VOCs and complying with all GBCSA requirements, our range of adhesives contains a number of solutions tailored to specific flooring choices.

The installation of resilient flooring calls for an evaluation of all the factors that play a role in the lifetime of the floor covering. iTe Products broadly categorises four main areas for consideration in identifying the correct flooring adhesive for your specific project.

Substrate Considerations, manufacturer regulations, environmental considerations and project specific considerations all play independently important roles in making an informed adhesive selection.

iTe Products® has addressed these important factors in developing the **GRIPiTe®** range of "fit for purpose" adhesives that meet all stringent technical requirements while at the same time satisfy ease of application to minimise any potential problems.



















PHYSICAL 7 Clarke Street South, Alrode, Alberton, 1457, South Africa POSTAL P.O. Box 17224, Randhart, 1457, South Africa TEL +27 (0)11 864 4918 FAX +27 (0)11 864 2123 sales@iteproducts.co.za www.iteproducts.co.za

Member of:



Belgotex











GRIPiTe® V10 is a pressure sensitive adhesive, designed for backed carpet tiles. GRIPiTe®V10 contains no VOC's and is therefore fully compliant with the GBCSA's requirements for a "Green" adhesive. GRIPiTe®V10 is available in 20Litre plastic containers.





GRIPiTe® V20 is a general-purpose carpeting adhesive, designed for needle punch broadloom and tiles. GRIPiTe® V20 is water based and contains no VOC's which fully complies with the GBCSA's requirements for a "Green" adhesive. GRIPiTe® V20 is available in 20 Litre plastic containers.





GRIPiTe®C60 Contact Adhesive is a powerful solvent free two-way stick adhesive. It has a short open time and is suitable for use with PVC or Vinvl Flooring, LVT's, Rubber Flooring, Needle Punch Carpeting and most floor and wall coverings. GRIPiTe®C60 is safe for use on many solvent-sensitive materials. GRIPiTe®C60 is non-fl ammable, solvent free and completely safe for use in confi ned, poorly ventilated areas and has a very low odour emission. GRIPiTe® C60 is not

harmful to the applicator. **GRIPiTe®C60** is water based and contains no VOC's.







GRIPiTe®C60SD Static Dissipative Contact Adhesive is a powerful solvent free two way stick adhesive with static dissipative properties. It has a relatively short open time with bonding capabilities for Vinyl Wall Cladding, Skirtings, profiles and floor coverings on absorbent and non-absorbent substrates internally.



STATIC DISSIPATIVE FLOORING ADHESIVE

GRIPiTe® V30 is a general-purpose vinvl flooring adhesive. Designed for semiflexible vinvl tiles as well as fully flexible vinyl tiles and sheeting. GRIPiTe® V30 is water based and contains no VOC's which fully complies with the GBCSA's requirements for a "Green" adhesive. GRIPiTe®V30 is available in 20 Litre plastic containers.

GRIPiTe® V30SD Static Dissipative and

Conductive Flooring Adhesive is a high

bond strength static dissipative floor

coverings adhesive. It has conductive

properties which enable the discharge

or dissipation of electrical charges

which build up in vinvl fl ooring to a

discharge earth leakage point. The

adhesive can be used with copper

or aluminium strips connected to an

earth leakage point. GRIPiTe® V30SD is

available in 20 Litre plastic containers.



GRIPiTe®V50 is a hard-set high performance specialised LVT (Luxury Vinvl Tile or Plank) adhesive. GRIPiTe® V50 is water based and contains no VOC's which fully complies with the GBCSA's requirements for a "Green" adhesive. GRIPiTe® V50 is available in 5 Litre and 20 Litre plastic containers.

HIGH-PERFORMANC





GRIPiTe®H80 is a one-part silicone modified polymer hybrid adhesive designed for bonding various materials such as Artificial Turf, Engineered Wood and Composite Rubber sports floors. GRIPiTe® H80 is moisture curing, which makes it resistant to any residual moisture in the concrete. GRIPiTe® H80 has very high bond strength and will prevent any delamination or breaking loose from the substrate provided there is no delamination in the substrate itself. The adhesive retains slight flexibility for its lifetime, and will not harden or break down.





The **GRIPiTe®** range of adhesives is manufactured to comply with the standards required for their specific uses.

Our warranty is based on the substrate being sound, dry and free of contamination. All application is to be carried out in strict compliance with the applicable data sheet as issued. The correct notched trowel is supplied with each bucket of adhesive.

iTe **Products**® further warrants that the products are manufactured to strict quality control standards and that the products supplied are free of defect. We cannot be held responsible for failure due to excessive moisture. flooding or the substrate failing for any reason, or application of the adhesive in a manner not suited to the circumstances.

