




tile house

presents the CREOS tile range



CREOS
melting colours





Bride

120x278/48"x110" R
120x120/48"x48" Soft R
60x120/24"x48" Soft R
75x75/30"x30" Soft R
60x60/24"x24" R
60x60/24"x24" Soft R
30x60/12"x24" R
30x60/12"x24" Soft R
45x45/18"x18" Soft



Dorian

120x278/48"x110" R
120x120/48"x48" Soft R
60x120/24"x48" Soft R
75x75/30"x30" Soft R
60x60/24"x24" R
60x60/24"x24" Soft R
30x60/12"x24" R
30x60/12"x24" Soft R
45x45/18"x18" Soft



Shadow

120x120/48"x48" Soft R
60x120/24"x48" Soft R
75x75/30"x30" Soft R
60x60/24"x24" R
60x60/24"x24" Soft R
30x60/12"x24" R
30x60/12"x24" Soft R
45x45/18"x18" Soft



Cookie

120x120/48"x48" Soft R
60x120/24"x48" Soft R
75x75/30"x30" Soft R
60x60/24"x24" R
60x60/24"x24" Soft R
30x60/12"x24" R
30x60/12"x24" Soft R
45x45/18"x18" Soft



Mud

120x120/48"x48" Soft R
60x120/24"x48" Soft R
75x75/30"x30" Soft R
60x60/24"x24" R
60x60/24"x24" Soft R
30x60/12"x24" R
30x60/12"x24" Soft R
45x45/18"x18" Soft





elegant colour
creating highly
expressive spaces



V2
Slight



Bluebay

120×278/48"×110" R
120×120/48"×48" Soft R
60×120/24"×48" Soft R
60×60/24"×24" Soft R
30×60/12"×24" Soft R

Coral

120×278/48"×110" R
120×120/48"×48" Soft R
60×120/24"×48" Soft R
60×60/24"×24" Soft R
30×60/12"×24" Soft R

Coral 120×120/48"×48" Soft R




A modern interior design featuring a bar and lounge area. The bar has a blue front and a wooden back with shelves for bottles. The lounge area has wooden tables, chairs, and a sofa. The walls are a mix of wood and blue. Large windows offer a view of the street outside.





Colour range

Colori/Colours/Couleurs/ Farben/Kleuren/Colores			Bride	Dorian
V2 Slight				
Formati Sizes Formats Formate Formaten Formatos	± 6 mm	120×278/48"×110" R		
	± 9 mm	120×120/48"×48" Soft R		
		60×120/24"×48" Soft R		
		75×75/30"×30" Soft R		
		60×60/24"×24" R		
		60×60/24"×24" Soft R		
		30×60/12"×24" R		
		30×60/12"×24" Soft R		
	± 9,5 mm	45×45/18"×18" Soft		
	± 9 mm battiscopa	7×75/2 ^{7/8} "×30" R		
		7×60/2 ^{7/8} "×24" R		

Shadow	Cookie	Mud	Bluebay	Coral
				
				
				
				
				
				
				
				
				
				
				
				


Creos
24/25

Legenda/Legend/Légende/Legende/Leyenda					
Gres Fine Porcellanato – EN 14411 ISO 13006 Gruppo Bla Annex G					
	Regulation	Required standards			
	Dimensioni/Sizes/Dimensions/ Abmessungen/Amfmetingen/ Dimensiones	UNI EN ISO 10545/2	Non rettificato Not rectified		
			Lunghezza e larghezza/Length and width/longueur et largeur/Länge und Breite/Lengte en breedte/ Longitud y anchura		
			± 0,6 % max 2 mm		
			± 0,3 % max 1		
			Spessore/Thickness/Épaisseur/ Stärke/Dikte/Grosor		
			± 5 % max 0,5 mm		
			± 5 % max C		
			Rettilineità spigoli/Linearity/ Rectitude des arêtes/ Kantengeradheit/Rachtheid kanter/ Rectitud de los lados		
			± 0,5 % max 1,5 mm		
			± 0,3 % max C		
			** Ortogonalità/Wedging/ Orthogonalité/Rechtwinkligkeit/ Haaksheid hoeken/Ortogonalidad		
			± 0,5 % max 2 mm		
			± 0,3 % max 1		
			Planarità/Warpage/Planéité/ Ebenfächigkeit/ Vlakheid/Planitud		
			± 0,5 % max 2 mm		
			± 0,4 % max 1		
	* According to ISO 13006.				
	Assorbimento acqua / Water absorption / Absorption d'eau / Wasseraufnahme / Waterabsorptie / Absorción de agua	UNI EN ISO 10545/3	≤ 0,5 %		
	Resistenza alla flessione / Flexual Strength/Resistance à la flexion / Biegefestigkeit / Buigvastheid / Resistencia a la flexión	UNI EN ISO 10545/4	≥ 35 N/mm ²		
			S ≥ 1300 N (thickness ≥ 7,5 mm)		
	Coefficiente di restituzione (COR) / Coefficient of restitution (COR) / Coefficient de restitution (COR) / Schlagfestigkeit (COR) / Restitutiecoëfficiënt (COR) / Coeficiente de restitución (COR)	UNI EN ISO 10545/5	Valore consigliato ≥ 0,55/ Recommended value ≥ 0,55/ Valeur recommandée ≥ 0,55/ Empfohlener Wert ≥ 0,55/ Aanbevolen waarde ≥ 0,55/ Rvalor recomendado ≥ 0,55		
	Resistenza all'abrasione profonda / Deep abrasion resistance / Résistance à l'abrasion / Widerstand gegen Tiefenverschleiß / Weerstand tegen afschuren / Resistencia a la abrasión profunda	UNI EN ISO 10545/6	≤ 175 mm ³		
	Resistenza all'abrasione/ Abrasion resistance/ Résistance à l'abrasion/ Abriebbeständigkeit/ Weerstand tegen afschuring/ Resistencia a la abrasión	UNI EN ISO 10545/7	PEI Solo per piastrelle smaltate / Only for glazed tiles		
	Coefficiente di dilatazione termica lineare / Coefficient of thermal linear expansion / Coefficient de dilatation thermique linear / Linearer Wärmeausdehnungskoeffizient / Lineaire thermische uitzetting / Coeficiente de dilatación termica linear	UNI EN ISO 10545/8	Metodo di prova disponibile / Tests method available / Methode d'essai disponible / Verfügbares / Prüfverfahren / Testmethode beschikbaar / Método de prueba disponible		
	Resistenza agli sbalzi termici / Thermal shock resistance / Résistance aux écarts de temperature / Temperatuurwisselbeständigkeit / Temperatuurswisseling / Resistencia al choque térmico	UNI EN ISO 10545/9	Nessun campione deve presentare difetti visibili / No sample must show visible defects / Aucun échantillon ne doit présenter des défauts visibles / Kein Exemplar darf sichtbare Schäden aufweisen / Geen enkel monster mag zichtbare gebreken vertonen / Ninguna muestra debe presentar defectos visibles		
	Dilatazione all'umidità / Moisture expansion / Dilatation à l'humidité / Feuchtigkeitsausdehnung / Uitzetting door vocht / Dilatación por la humedad	UNI EN ISO 10545/10	Metodo di prova disponibile / Tests method available / Methode d'essai disponible / Verfügbares / Prüfverfahren / Testmethode beschikbaar / Método de prueba disponible		
	Resistenza al fuoco / Fire resistance / Résistance au feu / Brandverhalten / Brand weerstand / Resistencia al fuego	UNI EN ISO 13501-1	Dichiarare un valore / Declaire a value Classe A1 oppure A ₁₄ / Class A1 or A ₁₄		

Legenda/Legend/Légende/Legende/Leyenda					Gres Fine Porcellanato – EN 14411 ISO 13006 Gruppo Bla Annex G				
	Regulation	Required standards							
	Resistenza all'attacco chimico / Chemical resistance / Résistance à l'attaque chimique / Beständigkeit gegen Chemikalien / Chemische bestandheid / Resistencia al ataque químico	UNI EN ISO 10545/13							
	Resistenza ai prodotti chimici di uso domestico ed agli additivi per piscina / Resistance to household chemicals and swimming pool salts	UNI EN ISO 10545/13	Classe minima B (GB per piastrelle smaltate) / Minimum class B (GB for glazed tiles)						
	Resistenza a basse concentrazioni di acidi e alcali / Resistance to low concentrations of acids and alkalis	UNI EN ISO 10545/13	Classe minima B (GB per piastrelle non smaltate) / Minimum class B (GB for unglazed tiles)			Dichiarare una classe / Declare a class			
	Resistenza ad alte concentrazioni di acidi e alcali / Resistance to high concentrations of acids and alkalis	UNI EN ISO 10545/13	Metodo di prova disponibile / Tests method available			Dichiarare una classe / Declare a class			
			Metodo di prova disponibile / Tests method available						
	Resistenza alle macchie / Stain resistance / Insensibilité aux taches / Beständigkeit gegen Fleckenbildner / Substanzen / Weerstand tegen vlekken / Resistencia a las manchas	UNI EN ISO 10545/14	UGL Dichiarare un valore / UGL Declare a value GL ≥ 3						
	Cessione di piombo e cadmio/ Lead and cadmium discharge/ Perte de plomb et cadmium/ Abgabe von Blei und Cadmium/ Ortidaan van lood en cadmium/ Cesión de plomo y cadmio	UNI EN ISO 10545/15	Valore dichiarato per piastrelle GL / Declared value for GL tiles						
	Indicazione di resistenza allo scivolamento / Assessment of slip resistance / Indication de la resistance au glissement / Bestimmung der Trittsicherheit / Indicate voor de slipvastheid / Indicación de resistencia al deslizamiento	DIN 51130 DIN 51097 BS 7976-2:2002 (CEN/TS 16165, Annex C) Pendulum Friction Test	Dichiarare un valore (R) / Declare a value (R) Dichiarare un valore (A+B+C) / Declare a value (A+B+C) Dichiarare un valore / Declare a value						
	Coefficiente di attrito dinamico / Measurement of dynamic coefficient of friction / Mesure du coefficient de frottement dynamique / Messung des dynamischen Reibungskoeffizienten / Meting van de dynamische wrijvingscoëfficiënt / Coeficiente de rozamiento dinámico	B.C.R.A. Rep. CEC/81 ANSI A137.1- 2012 (BOT3000)	Asciutto > 0,40 / Bagnato > 0,40 > 0,42 Wet						

**Per piastrelle rettangolari, che abbiano il lato maggiore L≥ 60 cm, e rapporto tra i lati ≥ 3, la misurazione della ortogonalità deve venire condotta solo
For oblong tiles with L≥ 60 cm and ratio length/width L/W≥3, measurement of rectangularity only on short edges

Color shading



The slight chromatic variation and the veining of the product is an intrinsic feature to re-create the randomness and richness of the colour shading of natural stones to which the collection is inspired. For these reasons, we recommend installing the product choosing tiles from different boxes in order to guarantee a variable and natural random effect of the finished surface. Due to these intrinsic features of the product, the colours represented in this catalogue must only be considered an example of the many possible colour shades.

Dorian 120×120/48"×48" Soft R



tile house

122 Marine Drive, Paarden Eiland, Cape Town

info@tilehouse.co.za

www.tilehouse.co.za

021 506 3020