

Page 1 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Toko Eco Proof

10569 Colltex Eco Skinproof 125ml 5582625 Eco Textile Proof 500ml 5582627 Eco Shoe Proof & Care 500ml

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Impregnator

Care product

Sector of use [SU]:

SU21 - Consumer uses: Private households (=general public = consumers)

Chemical product category [PC]:

PC34 - Textile dyes, and impregnating products

Environmental Release Category [ERC]:

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

SWIX SPORT GmbH, Junkersstr. 1, 82178 Puchheim, Germany Phone:(+49) 089 849369-21, Fax:(+49) 089 849369-13 info@swixsport.de, www.swix.de

Toko-Swix Sport AG Industriestrasse 4 CH-9450 Altstätten SG

Tel.: +41 (0)71 757 73 73 Fax: +41 (0)71 757 73 00

www.toko.ch

www.facebook.com/tokoworldwide

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (SWS)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard category **Hazard statement** Hazard class

H225-Highly flammable liquid and vapour. Flam. Liq. 2

2 Eve Irrit. H319-Causes serious eve irritation.

3 STOT SE H336-May cause drowsiness or dizziness.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear eye protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.

P501-Dispose of contents / container to special waste collection point.

Propan-2-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

* ······				
Propan-2-ol				
Registration number (REACH)	01-2119457558-25-XXXX			
Index	603-117-00-0			
EINECS, ELINCS, NLP	200-661-7			
CAS	67-63-0			
content %	80-100			
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225			
	Eye Irrit. 2, H319			
	STOT SE 3, H336			

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.



Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent

Thinners

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Watering eyes

If solvent components are inhaled above the air threshold-value:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Coordination disorders

Unconsciousness

With long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Skin resorption

4.3 Indication of any immediate medical attention and special treatment needed

Ingestion of large quantities:

Sodium sulphate laxative (1 table spoon and 1 glass of water) with generous amounts of activated charcoal.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Extinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon



Page 4 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

Formaldehyde Toxic gases

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Observe special storage conditions.

Protect from direct sunlight and warming.

Store in a well-ventilated place.

Store cool.

7.3 Specific end use(s)

No information available at present.



ദ

Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

©® Chemical Name	Propan-2-ol	Content %:80- 100
WEL-TWA: 400 ppm (999 mg/n	(3) WEL-STEL: 500 ppm (1250 mg/m3)	-
Monitoring procedures:	 Compur - KITA-122 SA(C) (549 277) 	
	 Compur - KITA-150 U (550 382) 	
	 Draeger - Alcohol 25/a i-Propanol (81 01 631) 	
	DFG (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtur	res 6) - 1998, 2002 -
	 EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) 	
	 Draeger - Alcohol 100/a (CH 29 701) 	
BMGV:	Other information:	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period)
 EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Propan-2-ol						
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment,		PNEC	552	mg/kg	
	freshwater					
	Environment - sediment,		PNEC	552	mg/kg	
	marine					
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage		PNEC	2251	mg/l	
	treatment plant					
	Environment - water,		PNEC	140,9	mg/l	
	sporadic (intermittent)					
	release					
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m3	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m3	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".



Page 6 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Safety gloves made of butyl (EN 374)

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective Viton® / fluoroelastomer gloves (EN 374)

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

pH-value:

Liquid

Clear

Alcoholic

Not determined

Not determined

pH-value:

Melting point/freezing point:

Not determined

Not determined

Initial boiling point and boiling range:

Not determined

Flash point: 12 - 14 °C (Propan-2-ol)

Evaporation rate:

Flammability (solid, gas):

Not determined

Not determined

Lower explosive limit: 2 Vol-% (20°C, Propan-2-ol)



Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

Upper explosive limit: 12 Vol-% (Propan-2-ol) Vapour pressure: 42 - 48 hPa (Propan-2-ol)

Vapour density (air = 1): Not determined

Density: 0,75 - 0,85 g/cm3 (20°C) Bulk density: n.a.

Solubility(ies):

Not determined

Water solubility: Mixable

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Not determined
425 °C (Propan-2-ol)

Decomposition temperature:

Viscosity:

Not determined

Not determined

Explosive properties: Product is not explosive. When using: development of explosive

Nο

vapour/air mixture possible.

Oxidising properties:

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Surface tension:

Solvents content:

Not determined
Not determined
Not determined
Not determined
Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

Amines

Bases

Acids

Oxidizing agents

Peroxides

Alkali metals

Alkaline-earth metals

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toko Eco Proof						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						



Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006 Valid from: 19.01.2018

PDF print date: 19.01.2018

Toko Eco Proof

Germ cell mutagenicity:			n.d.a.
Carcinogenicity:			n.d.a.
Reproductive toxicity:			n.d.a.
Specific target organ toxicity -			n.d.a.
single exposure (STOT-SE):			
Specific target organ toxicity -			n.d.a.
repeated exposure (STOT-			
RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Symptoms:						breathing difficulties, unconsciousnes s, vomiting, headaches, fatigue, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toko Eco Proof							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							



Page 9 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

12.6. Other adverse				n.d.a.
effects:				

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna	,	
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	BOD		1171	mg/g			
12.4. Mobility in soil:	Koc		1,1				Expert judgement
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 02 plastic packaging

SECTION 14: Transport information

1219

General statements

14.1. UN number:



Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
UN 1219 ISOPROPANOL, MIXTURE
14.3. Transport hazard class(es):

14.3. Transport hazard class(es):314.4. Packing group:IIClassification code:F1LQ:1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D/E

Transport by sea (IMDG-code)

14.2. UN proper shipping name: ISOPROPANOL, MIXTURE 14.3. Transport hazard class(es): 14.4. Packing group: EmS:

14.4. Packing group:IIEmS:F-E, S-DMarine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Isopropanol mixture

14.3. Transport hazard class(es):

14.4. Packing group:

II

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

3

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

	,		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): < 98,8 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information







Page 11 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

Revised sections:

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

1

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Flam. Lig. — Flammable liquid

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration



Page 12 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene



Page 13 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2018 / 0007

Replacing version dated / version: 07.03.2017 / 0006

Valid from: 19.01.2018 PDF print date: 19.01.2018

Toko Eco Proof

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning

the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.