

Delock USB 3.2 Gen 2 Enclosure for PlayStation®5 with M.2 NVMe Slot - tool free

Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280, 2260 and 2242 format. It connects directly to the **PS5** with the two USB Type-A connectors. The **robust metal housing with air vents** at the sides ensures an optimum temperature of the memory.

Additional USB Type-A port

This port is directly forwarded from the PlayStation®. Thus, the USB Type-A port on the enclosure can still be used **to connect additional USB devices** or to **charge the game console's controller**.

USB extension cable

The included extension cable can be used to **connect the enclosure to a PlayStation®4** and thus copy games to the M.2 SSD to use them on the PS5. Furthermore, the cable can be used to connect the enclosure to a PC or laptop.

SSD installation without tools

The special feature of this enclosure is that **no tools** are required to install the M.2 SSD. The lid can be pushed backwards by a little pressure, the SSD will be attached to the PCB with a rubber nipple and then the lid is reattached until it locks.



Specification

- Connectors:
 - external:
 - 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A male
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female
 - internal: 1 x 67 pin M.2 key M slot
- Supports M.2 modules in format 2280, 2260 and 2242 with key M or key B+M based on SATA or PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Supports UASP
- Supports TRIM
- Supports S.M.A.R.T.
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Metal housing
- Dimensions (LxWxH): ca. 120 x 45 x 15 mm
- Hot Plug, Plug & Play

System requirements

- PlayStation®5
- PlayStation®4 (with cable)
- Windows 10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- External enclosure M.2
- Cable USB Type-A male to Type-A female, length ca. 30 cm
- 2 x thermal conductive pad
- 1 x thermal conductive plate

Item no. 42013

EAN: 4043619420131

Country of origin: China

Package: Retail Box

- 2 x rubber nipple
- User manual

Images



General	
Function:	NVM Express (NVMe) Hot Plug Plug & Play TRIM S.M.A.R.T.
Supported operating system:	Windows 10 32-bit Windows 10 64-bit Windows 11 PlayStation®5
Supported module:	Supports M.2 modules in format 2280, 2260 and 2242 with key M or key B+M based on SATA or PCIe (NVMe)
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported
Interface	
External:	1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A male
Internal:	1 x 67 pin M.2 key M slot
Technical characteristics	
Data transfer rate:	10 Gbps
Physical characteristics	
Housing material:	metal
Cable length:	30 cm
Length:	125 mm
Width:	45 mm
Height:	15 mm