

PRODUCT DATASHEET

DOWNLIGHT SLIM 85mm 4.5W 6500K

RECESS SLIM DOWNLIGHT | Recess slim downlight with integrated driver



AREAS OF APPLICATION

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms
- Kitchens

PRODUCT BENEFITS

- Very slim design
- Ideal when few space in the ceiling

PRODUCT FEATURES

- Housing material: plastic
- Integrated driver



TECHNICAL DATA

Electrical data

Nominal wattage	4.50 W
Operating mode	External LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	6500 K
Color rendering index Ra	≥80
Light color (designation)	Cool Daylight
Luminous flux	240 lm
Luminous efficacy	56 lm/W

Light technical data

Beam angle	110 °
------------	-------

Luminaire sensor data

Type of sensor	-
----------------	---

Dimensions & weight

Diameter	85.0 mm
Height	37.0 mm
Product weight	60.00 g

Colors & materials

Body material	POLYPROPYLENE (PP)/POLYAMID
Product color	White
Housing color	White

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Number of switching cycles	15000
Lifespan	25000 h

Additional product data

Mounting type	Recessed
Mounting location	Ceiling

Capabilities

Dimmable	No
Type of connection	Screw terminal
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE/ERP/RoHS/REACH

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075573178	Folding carton box 1	97 mm x 97 mm x 57 mm	83.00 g	0.54 dm ³
4058075573185	Shipping carton box 6	206 mm x 108 mm x 190 mm	888.00 g	4.23 dm ³
4058075643000	Shipping carton box 36	- x - x -		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.