

PRODUCT DATASHEETDOWNLIGHT SLIM 120mm 8W 4000K

RECESS SLIM DOWNLIGHT | Recess slim downlight with integrated driver



AREAS OF APPLICATION

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms
- Kitchens

PRODUCT BENEFITS

- Very slim design
- Ideal when few space in the ceiling

PRODUCT FEATURES

- Housing material: plastic
- Integrated driver



TECHNICAL DATA

Electrical data

Nominal wattage	8.00 W	
Operating mode	External LED driver	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	

Photometrical data

Color temperature	4000 K
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	550 lm
Luminous efficacy	70 lm/W

Light technical data

Beam angle	110 °
· · · · · · · · · · · · · · · · · · ·	

Luminaire sensor data

Type of sensor	-
----------------	---

Dimensions & weight

	Diameter	120.0 mm
Ī	Height	35.0 mm
Ī	Product weight	99.00 g

Colors & materials

Body material	POLYPROPHYLENE (PP)/POLYAMID	
Product color	White	
Housing color	White	

Temperatures & operating conditions

Lifespan

Number of switching cycles	15000
Lifespan	25000 h

Additional product data

Mounting type	Recessed
Mounting location	Ceiling

Capabilities

Dimmable	No	
Type of connection	Screw terminal	
LED module replaceable	Not replaceable	

Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE/ERP/RoHS/REACH

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075573130	Folding carton box 1	85 mm x 64 mm x 96 mm	123.00 g	0.52 dm ³
4058075642744	Shipping carton box 6	266 mm x 138 mm x 200 mm	1626.00 g	7.34 dm ³
4058075642751	Shipping carton box 24	550 mm x 294 mm x 217 mm	9350.00 g	35.09 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.