

# DIGITUS 4K HDMI Switch to DisplayPort Adapter

AK-330101-002-S  
EAN 4016032481102



**HDMI M to DP F with external Power 4K@30Hz. 0,2 m Black**

- Supports: 2K ( @30Hz.
- Supports: 4K (3840 x 2160) @30Hz.
- Supports data transfer rates of up to 40 Gbit/s
- Backwards-compatible with Thunderbolt 3, USB 3.2, USB 3.1 and USB 2.0
- Supports USB Power Delivery Revision 3.0 (PD 3.0) with 20 V, 5A and 100W
- Strand material: CU
- Connection 1: USB Type-C, plug
- Connection 2: USB Type-C, plug
- Dimensions plug 1: 6.65\*2.4mm
- Dimensions plug 2: 6.65\*2.4mm
- Color of connections: black
- Contact material: nickel-plated
- Contact surface: gold-plated
- Number of PINS: 22
- Hood: cast
- External cable material: TPE
- Exterior cable diameter: 5.0 mm

- Tensile strength: 4 kg/min
- AWG: 30
- Length: 0.8 m
- Bending radius: 60
- Cable color: black
- Shielding: double shielding
- USB-C product: no
- Total weight: 45 g
- Manufacturer's notice:
- If you connect a USB-C monitor/TV/projector to a PC equipped with USB Type-C, make sure that your USB-C display supports DisplayPort signal output.
- The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution.
- In order to use a dual 4K output, the USB 4 device must support the PD3.0 protocol
- AOC - Active Optical Cable: no

**Package contents**

- 1x USB Type-C <=> DisplayPort Bi-Directional Adapter Cable

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	300	1.14	32.00	50.00	21.00	33,600.00
Packaging Unit Inside	10	0.04	4.00	30.00	20.00	2,400.00
Packaging Unit Single	1	0.00	2.00	23.90	116.00	5,544.80
Net single without Packaging	1	0.04	0.60	21.00	11.50	144.90

More images:

